

CHIPPING HAMMERS



Applications

- Used for construction and industrial applications including chipping and scaling

Features

- Complete line of hammers
- Strong and reliable
- All models equipped with mufflers for noise reduction
- Vibration-reduced, silenced (SVR) models available

Pneumatic Chipping Hammers	CP 0012	CP 0012-2	CP 0012-2
Weight kg	5.5 (12)	5.5 (12)	5.5 (12)
Length mm	406 (15.9)	406 (15.9)	406 (15.9)
Air Consumption l/s	9.5 (20)	9.5 (20)	9.5 (20)
Blows Per Minute bpm	2,580	2,580	2,580
Vibration Level 3 Axes (ISO 28927-10) m/s ²	14.6	14.6	14.6
Sound Power Level Guaranteed (2000/14/EC) dB(A)	104	104	104
Sound Pressure Level (ISO 11203) dB(A)	89	89	89
Retainer Type	Screw Cap	Spring Retainer	Spring Retainer
Air Inlet	3/8" BSP	3/8" NPTF	3/8" NPTF
D-Handle Type	Inside Trigger	Inside Trigger	Inside Trigger
Part Number Chuck Size mm	8900 0001 01 Hex 19 x 50 (3/4 x 2)	8900 0001 02* Rd 17.3 (0.680)	8900 0001 03* Hex 14.7 (0.580)

*Not for sale within EU/EEA

NOTE: All values measured at 6 bar (87 psi) except sound data, which was measured at 6.2 bar (89 psi).

Pneumatic Chipping Hammers	CP 4123 - 2	CP 4123 - 2	CP 4123 - 3	CP 4123 - 3	CP 4123 - 4	CP 4123 - 4	CP 4125 - 2	CP 4125 - 2	CP 4125 - 3
Weight kg (lb)	7 (15)	7 (15)	7.5 (17)	7.5 (17)	8 (18)	8 (18)	7 (15)	7 (15)	7.5 (17)
Length mm (in)	375 (14.8)	375 (14.8)	425 (16.7)	425 (16.7)	460 (18.1)	460 (18.1)	380 (15)	380 (15)	415 (16.3)
Air Consumption l/s (cfm)	12 (25)	12 (25)	14 (30)	14 (30)	13 (28)	13 (28)	13 (28)	13 (28)	15 (32)
Blows Per Minute bpm	2,220	2,220	1,800	1,800	1,440	1,440	1,920	1,920	1,680
Vibration Level 3 Axes** (ISO 28927-10) m/s ²	13.2	13.2	11.4	11.4	13.9	13.9	13.8	13.8	15.3
Sound Power Level Guaranteed** (2000/14/EC) dB(A)	—	—	—	—	—	—	—	—	—
Sound Pressure Level (ISO 11203) dB(A)	—	—	—	—	—	—	—	—	—
Air Inlet	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF
Handle Type	Pistol Grip	Pistol Grip	Pistol Grip	Pistol Grip	Pistol Grip	Pistol Grip	Pistol Grip	Pistol Grip	Pistol Grip
Part Number ⁽¹⁾ Chuck Size mm (in)	8900 0001 04 Rd 17.3 (0.680)	8900 0001 05 Hex 14.7 (0.580)	8900 0001 06 Rd 17.3 (0.680)	8900 0001 07 Hex 14.7 (0.580)	8900 0001 08 Rd 17.3 (0.680)	8900 0001 09 Hex 14.7 (0.580)	8900 0001 10 Rd 17.3 (0.680)	8900 0001 11 Hex 14.7 (0.580)	8900 0001 12 Rd 17.3 (0.680)

Pneumatic Chipping Hammers	CP 4125 - 3	CP 4125 - 4	CP 4125 - 4	CP 4130 - 3	CP 4130 - 3	CP 4130 - 4	CP 4130 4H
Weight kg (lb)	7.5 (17)	8 (18)	8 (18)	8.5 (19)	8.5 (19)	9 (20)	9 (20)
Length mm (in)	415 (16.3)	445 (17.5)	445 (17.5)	420 (16.5)	420 (16.5)	450 (17.7)	450 (17.7)
Air Consumption l/s (cfm)	15 (32)	13 (28)	13 (28)	12 (25)	12 (25)	12.5 (26)	12.5 (26)
Blows Per Minute bpm	1,680	1,440	1,440	1,920	1,920	1,500	1,500
Vibration Level 3 Axes (ISO 28927-10) m/s ²	15.3	14.6	14.6	9.6	9.6	12.3	12.3
Sound Power Level Guaranteed (2000/14/EC) dB(A)	—	—	—	104	104	104	104
Sound Pressure Level (ISO 11203) dB(A)	—	—	—	90	90	90	90
Air Inlet	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF	3/8" NPTF
Handle Type	Pistol Grip	Pistol Grip	Pistol Grip	D-Handle, Outside Trigger	D-Handle, Outside Trigger	D-Handle, Outside Trigger	D-Handle, Outside Trigger
Part Number ⁽¹⁾ Chuck Size mm (in)	8900 0001 13 Hex 14.7 (0.580)	8900 0001 14 Rd 17.3 (0.680)	8900 0001 15 Hex 14.7 (0.580)	8900 0001 16 Rd 17.3 (0.680)	8900 0001 17 Hex 14.7 (0.580)	8900 0001 18 Rd 17.3 (0.680)	8900 0001 19 Hex 14.7 (0.580)

⁽¹⁾ spring retainer

NOTE: All values measured at 6 bar (87 psi) except sound data, which was measured at 6.2 bar (89 psi).