





## GERMAN TYPE MACHINIST'S HAMMER







COD.		L (mm)	A (mm)	B (mm)	C (mm)		
69618	200	275	20	96	21	6	●
69619	300	305	23	103	23		
69620	400		27	118	28		
69621	500	325	29	123	31		
69622	600		33	128	32		
69675	800	340	37	135	37		
69676	1000	355					



### TECHNICAL SPECIFICATION

Hickory wood




COD.		L (mm)	A (mm)	B (mm)	C (mm)		
69731	200	255	20	96	21	6	●
69732	300	275	23	103	23		
69733	400		27	118	28		
69734	500	300	29	123	31		
69735	600		33	128	32		
69736	800	350	37	135	37		
69737	1000						






### TECHNICAL SPECIFICATION

Fiberglass

## JOINER'S HAMMER



COD.		L (mm)	A (mm)	B (mm)	C (mm)		
69601	150	270	18	88	17	6	●
69602	200		20	93	19		
69603	250		22	97	23		
69604	350	300	25	107	24		
69681	450		28	116	27		
69682	550	310	30	121	29		



The carpenter's hammer head is formed with one squared end and one narrow end for use with small nails and pins, to reduce the risk of contact with fingers and causing damage to the work piece.

### TECHNICAL SPECIFICATION

Hickory wood