


## Hot water high-pressure cleaners

### Sundek 5Y LP



#### Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (three phase models)
- Three ceramic coated pistons, brass linear pump head (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve
- Vertical burner with high thermal efficiency steel coil.
- Suction and delivery S/S valves.
- Safety valve
- Temperature regulation gauge
- Glycerine pressure gauge.
- Automatic Stop System late shut down protection 24V.
- Adjustable detergent delivery with built-in tank for indirect suction.
- Auxiliary motor for burner air-cooling
- Two ways fuel pump
- Low fuel lamp
- Ergonomic handles and impact resistant covers
- Accessory holder
- Power cable (m 5).



#### Standard equipment:

3.700.0030



3.708.0001



3.103.0050 - mod. 1311 - 2015  
3.103.0051 - mod. 1515



4.618.0143 - 10 m.



#### Optional:

- Hose-reel with brake code 6.608.0077
- Antiscale LC-PRECAL (pcs. 4 x 5 lt.) code 3.697.0044

|                      | Sundek 5Y 1311 LP | Sundek 5Y 1515 LP | Sundek 5Y 2015 LP |
|----------------------|-------------------|-------------------|-------------------|
| Code                 | 8.621.2948        | 8.621.2942        | 8.621.2943        |
| Operat. pressure bar | 30 ÷ 110          | 30 ÷ 150          | 30 ÷ 200          |
| Operat. pressure psi | 1595              | 2175              | 2900              |
| Delivery rate l/h    | 330 ÷ 660         | 450 ÷ 900         | 450 ÷ 900         |
| Temp. max            | 140°C             | 140°C             | 140°C             |
| Power ass. W         | 3000              | 5500              | 7300              |
| RPM                  | 1450              | 1450              | 1450              |
| Voltage              | 230 V~50 Hz       | 400 V~50 Hz       | 400 V~50 Hz       |