

**P 2000 G (600962000) Garden pump**  
**(220-240 V / 50 Hz); Cardboard box**

Order no. 600962000  
EAN 4007430240750



Product may differ from Image



- For garden irrigation and groundwater pumping as well as pumping, pumping empty, circulation of clear water
- Maintenance-free capacitor motor
- Overload protection: protects the motor from overheating
- High-quality slip seal system for long service life
- Separate water filling opening for simple operation of the pump
- Water drain plug (removable without tools) for protection in case of frost
- Rubberised feet for low-noise and low-vibration operation
- Ergonomic handle for comfortable transport
- For garden irrigation with 1 or 2 sprinklers

## Technical data

### Characteristics

|                         |                                                   |
|-------------------------|---------------------------------------------------|
| Rated input power       | 450 W                                             |
| Maximum delivery rate   | 2000 l/h / 528 gal/h                              |
| Maximum delivery height | 30 m / 98 ft                                      |
| Maximum pressure        | 3 bar / 43.5 psi                                  |
| Maximum suction height  | 8 m / 26 ft                                       |
| Suction port            | 1" female thread                                  |
| Discharge port          | 1" female thread                                  |
| Pump housing            | Grey cast iron                                    |
| Protection type IP      | IP X4                                             |
| Drive shaft             | Stainless steel                                   |
| Number of impellers     | 1                                                 |
| Dimensions              | 350 x 190 x 260 mm // 13 25/32 x 7 1/2 x 10 1/4 " |
| Weight                  | 7.6 kg / 16.8 lbs                                 |
| Cable length            | 1.5 m / 5 ft                                      |

### Noise emission

|                              |            |
|------------------------------|------------|
| Sound pressure level         | 60 dB(A)   |
| Sound power level (LwA)      | 71.9 dB(A) |
| Uncertainty of measurement K | 3 dB(A)    |

## Scope of delivery

Fabric Sealing Tape