

		PRODUCT SPECIFICATION		ARTICLE OS6406 K S3 BLACK	
ArticleOS6406/1 K S3 Weight1,120 Kg ColorSIZE 42 BLACK		Description of the article: safety shoe, ankle model, full grain leather, lining CAMBRELLA, double density outsole in Pu, composite toecap and non metal midsole.		SECURITY CATEGORY S3SRC	
TECHNICAL DETAILS				IMAGE	
Type of PPE		Safety shoe for professional use in compliance with low EN ISO 20345:2011			
Main features		Black low model of safety shoe in full grain leather, Double layer sole in soft latex, antistatic, anti bacterial with SANITIZED treatment, lined in breathable and high scratch resistant fabric. Mesh Cambrella lining, good breathable. Black stitching. Black laces and plastic eyelets. composite toecap, resistant up to 200 J. non metallic midsole,. Test results: resistance improved more than 20% to nail's Perforation (diameter 4,5mm) comparable to a strength of 1360 N instead of 1100 N requested by EN 12568. Double density outsole, antistatic, anti spilt, resistant to oil spilt and, injected on the upper. - First injection in PU of grey color. Shock absorber main features. - Land outsole very resistant in PU..			
Security category		S3			
Law		CE UNI EN ISO20345:2011 – SAFETY SHOES			
Main features		UNI EN ISO 20345:2011 – Safety shoe with toe capacity resistance up to 200 J ENV 13287:2000 – Anti slip resistance Directive 1907/2006/CE – Determination of dangerous substances for leather and fabric elements. Directive 1907/2006/CE – Determination of the level of nickel for the metal parts in contact with the foot.			
		This safety shoe S3SRC is in compliance with the law EN 20345:2011			
Manufactured by		CALZATURIFICIO 5BI-ITALY			

