

Hot water high-pressure
cleaners

Sundek 5 XP



Equipped with:

- Three ceramic coated pistons, brass axial pump head with built-in bypass valve.
- Vertical burner with high thermal efficiency steel coil
- Suction and delivery S/S valves.
- Safety valve.
- Temperature regulation gauge.
- Glycerine pressure gauge.
- Automatic Stop System late shut down protection 24V.
- Adjustable detergent delivery with built-in tank for indirect suction.
- Two ways fuel pump
- Low fuel lamp.
- Ergonomic handles and impact resistant covers.
- Accessory holder.

Standard equipment:



Optional:

- Hose-reel with brake code 6.608.0001
- Header tank
- Antiscale LC-PRECAL (pcs. 4 x 5 lt. code 3.697.0044)



OPTIONAL

Hose reel with brake
code 6.608.0001

	Sundek 5 1211 XP	Sundek 5 1511 XP
Code	8.620.0606	8.620.0607
Operat. pressure bar	30 ÷ 120	30 ÷ 150
Operat. pressure psi	1740	2175
Delivery rate l/h	330 ÷ 660	330 ÷ 660
Temp. max	140°C	140°C
Power ass. W	3200	4000
RPM	2800	2800
Voltage	230 V~50 Hz	400 V~50 Hz