

| | | | | | |
|---|--|---|--|--|--|
|  | | PRODUCT SPECIFICATION | | ARTICLE L2815 SB BLACK | |
| Article L2815 SB Weight 1,100 Kg SIZE 42 Color white | | Description of the article: safety shoe, low model, microfiber, lining sinthetic, double density outsole in Pu, steel toe cap | | SECURITY CATEGORY S1SRC | |
| TECHNICAL DETAILS | | | | IMAGE | |
| Type of PPE | | Safety shoe for professional use in compliance with low EN ISO 20345:2011 | | | |
| Main features | | Black model of safety shoe in microfiber, Double layer sole in soft latex, antistatic, anti bacterial with SANITIZED treatment, lined in breathable and high scratch resistant fabric. Mesh Cambrella lining, good breathable. Black stitching. Steel toe, resistant up to 200 J. Double density outsole, antistatic, anti spilt, resistant to oil spilt and, injected on the upper. - First injection in PU of black color. Shock absorber main features. - Land outsole very resistant in PU.. | | | |
| Security category | | SB | | | |
| Law | | CE UNI EN ISO20345:2011 – SAFETY SHOES | | | |
| Main features | | UNI EN ISO 20345:2011 – Safety shoe with toe capacity resistance up to 200 J ENV 13287:2000 – Anti slip resistance Directive 1907/2006/CE – Determination of dangerous substances for leather and fabric elements. Directive 1907/2006/CE – Determination of the level of nickel for the metal parts in contact with the foot. | | | |
| | | This safety shoe SBSRC is in compliance with the law EN 20345:2011 | | | |
| Manufactured by | | CALZATURIFICIO 5BI | | | |

