

Cold water high-pressure cleaners

Tapi LP



Standard equipment:

0.966.0003 (mod. 2521)

0.966.0004 (mod. 3518)



0.966.0007 (mod.2521)

0.966.0008 (mod.3518)



0.966.0037 (mod. 3518)

0.966.0036 (mod. 2521)



0.966.0011 (mod.2521)

0.966.0012 (mod.3518)

10 m.



Equipped with:

- Motor 12-15 hp • Heavy duty structure with stainless steel covers
- High filtering capacity cartridge suction brass filter • TW Triplex Premium pumps • Pressure gauge with stainless steel casing
- Hot water seals 4-poles (1400 rpm) motor well oversized and protected with paint. Ø 300 wheels with brake • Highly professional unloader valve with external bypass • Motor-pump with flexible joint • Timed Total Stop • Low voltage control panel
- Contactor • Thermal relay motor protection • Hose reel with 20 mt hose can be mounted on request (cod. 0.966.0033 mod. 2521/cod. 0.966.0034 mod. 3518) • Practical and safe housing accessories

Optional:

Rotox lance

0.966.0014 (mod. 2521)

0.966.0015 (mod. 3518)

Pipe cleaning hose 25 m.

0.966.0020 (mod. 2521)

0.966.0021 (mod.3518)

Extension hose 10 m.

0.966.0024 (mod. 2521)

0.966.0025 (mod. 3518)

Sand-blasting lance 500 bar

0.966.0028 (mod. 2521)

0.966.0029 (mod. 3518)

	Tapi 2521 LP	Tapi 3518 LP
Code	0.066.0006	0.066.0007
Operat. pressure bar	250	350
Operat. pressure psi	3626	5076
Delivery rate l/h	1260	1080
Absorbed power W	10000	12000
RPM	1400	1400
Voltage	415V~50Hz	415V~50Hz