

VISOR TORIC CLEAR



COLORLESS VISOR TORIC

Ref. VISORTOIN



Product specifications

Polycarbonate injected visor. Thickness 1,9/2,0 mm. Electric Arc protection. Universal fixing. Suitable for faceshield holder VISOR HOLDER, VISOR-H, VISOR-U. 39 x 20 cm.

Polycarbonate

COLOUR

Clear

SIZE

No size

Product Use - Risks



Heat



Shock



UV / IR



Construction / Civil engineering



Heavy industry



Light industry

Product's highlights & user's benefits



Marking (EN166)
1 = the best optical class
A = highest shock resistance
T = extreme temperature resistance
8 = electrical Arc, short-circuit resistance
9 = molten metal projections resistance
Marking (EN170)
2C-1,2 = UV resistance

Anti-scratch

Durée de vie augmentée

Visière sphérique

Champ de vision extra large

Polycarbonate injecté

Résistance maximale à l'impact



Anti-scratch

Certifications and Standards



PPE DIRECTIVE EC 89/686

EN166 Personal eye-protection - Specifications
1AT 89: Oculars marking

EN170:2002 Ultraviolet filters
UV 2C-1.2: echelon

References

References	Bar code	COLOUR	SIZE
VISORTOIN	3295249137496	Clear	No size