

TESTING PUMPS

The Ega Master's Testing Pumps have an **exclusive and innovative valve system**, which increases its stiffness and stability, as well as the comfort and efficiency of the user, since it allows its complete use by applying only one hand.

There are 3 types of pumps, **horizontal, vertical and stainless steel**.



Maximum stability!

*12M: 12 MONTHS OF WARRANTY

1. Indispensable to verify the sealing in plumbing, heating, solar panels, fire-prevention equipments, in refrigeration systems, gas-oil installations, in boilers' and pressure container's building.



2. Quick pressure adjustment system by a single valve.

3. Hermeticity and pressure test with water or oil.

4. Easy reading pressure gauge.

5. Metallic construction, robust for the heavy plumbing work. Tank made in steel (or stainless steel), corrosion resistant, epoxy-powder coated up to 12 litres capacity.

6. Pressure hose included.

INSTRUCTIONS FOR USE



1-Fill up the tank



2-Connect the circuit



3- Pump until reaching the pressure



4-Wait the testing time

HORIZONTAL TESTING PUMP

COD.	CAP. L	Máx.	Conex. (inch)	Kg	
60005	12	60=860 Psi	1/2	7,7	1
60009		100=1440 Psi			

12M



COD.	CAP. L	Máx.	Conex. (inch)	Kg	
60011	12	60=860 Psi	1/2	7,7	1
60012		100=1440 Psi			

12M



Stainless steel

FEATURES

Stainless steel

VERTICAL TESTING PUMP

COD.	CAP. L	Máx.	Conex. (inch)	Kg	
60010	12	100=1440 Psi	1/2	9,0	1

12M



TECHNICAL SPECIFICATION

Quick pressure adjust system with just one valve	•
Maximum establiity	•
Capacity 12 l.	•
Easy-reading manometer	•
Pressure hose included	•
Comfortable use	•

TECHNICAL SPECIFICATION

Tank	60005, 60009	Sheet steel painted in epoxy-powder semi-texturized red color RAL 2002
	60011, 60012	Stainless steel sheet
	60010	Sheet steel painted in epoxy-powder semi-texturized red color RAL 2002
Valve		Bronze
Activation lever		Galvanised
Pressure gauge		0-60 BAR (0-860 Psi) 0-100 BAR (0-1440 Psi)
Pressure gauge connection		1/4" BSP
Outlet tube connection		1/2" BSP
Hose with 2 connections		1/2" BSP
Hose's length		1,5 m
Hose's diameter		Exterior: 18 mm Interior: 3/8"
Tank,s capacity		12 L

12M 12 MONTHS OF WARRANTY