



Fine Finish Low Pressure RAC X FF LP SwitchTip, 312

Part Number: FFLP312

Features

For fine finish applications

- Less Prep & Cleanup Time
 - Less mess with less overspray
 - Put the paint where you want it
- Easiest Pattern Overlap
 - Softer spray fan pattern
 - Easy to apply any material to any surface
 - Consistent blended finish quality
- Extended Life
 - Spraying at half pressure doubles tip life
 - Reduced sprayer maintenance – up to 2X life
- SmartTip Technology
 - Exclusive internal tip geometry
 - Reduces energy required to atomize paints, stains, and other materials
 - Delivers a superior finish with less pressure
 - Works with SmartControl on select Graco sprayers
- Best Tip on the Market
 - Works with any airless sprayer
 - Longest lasting fann pattern
 - Highest quality finish with a consistent spray pattern
- Easy to Identify Tip Size
 - Large raised tip size numbers are always legible – even when covered with paint

- Superior Tip Design
 - Locking tab ensures tip stays securely in guard
 - Snaps tip in spray or reverse position
 - OneSeal tip gasket installs with no tools
 - Solvent seal available when using extremely hot solvents

Specifications & Documents

Technical Specifications

| | |
|--------------------------------|---|
| Compatible Material | Primer, Stains, Varnish, Water-Based Paint, Enamel, Latex, Solventborne Paints |
| For Use With | RAC X HandTite Tip Guard |
| Material | Tungsten Carbide |
| Maximum Fan Width (in) | 6 |
| Maximum Flow Rate (GPM) | 0.15 |
| Maximum Working Pressure (psi) | 4050 |
| Minimum Fan Width (in) | 6 |
| Model | RAC X |
| Orifice Diameter (in) | 0.012 |
| Pattern Size (in) | 6 to 8 |
| Series | FF LP SwitchTip |
| Spray Pattern | Fan |
| Tip Type | Airless |
| Type | Spray Tip |

Product Manuals

[3A5432C, LP Warning Insert, English, Multilingual](#)