

## W 13-125 Quick (603627000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box; with quick-locking nut

Order no. 603627000 EAN 4061792176614



Product may differ from Image









- Long service life for demanding applications: powerful and robust angle grinder with highest power density in its class for quick work progress
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Restart protection after power interruption
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data	
Characteristics	
Disc-Ø	125 mm // 5 "
Rated input power	1350 W
Output power	830 W
No-load speed	11000 rpm
Speed at rated load	8000 rpm
Torque	3.4 Nm / 30.1 in-lbs
Spindle thread	M 14
Handle circumference	206 mm / 8 1/8 "
Weight (without power cable)	2.4 kg / 5.3 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	6 m/s²
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Inner support flange

M-Quick flange nut

www.metabo.com 2 / 2