

BP 4R

BETONEIRA PROFISSIONAL REBOCÁVEL
HORMIGONERA PROFESIONAL REMOLCABLE
BÉTONNIÈRE PROFESSIONNELLE TRACTABLE
PROFI ANHÄNGBARER BETONMISCHER
PROFESSIONAL TOWABLE CEMENT MIXER



Eixo flexível

Eje Flexible

Axe Flexible

Flexiblerachse

Flexible axis

Cremalheira e carreto em ferro fundido

Corona y piñon en hierro fundido

Couronne et pignon en fonte

Zahnkranz aus Gußeisen

Cast iron gear ring

LUBRIFICADOR
 ENGRASADOR
 GRAISSEUR
 SCHMIERNIPPEL
 LUBRICATION POINT

BOCA REFORÇADA
 BALDE COM 3 AMASSADORES DUPLOS SOLDADOS
 BOCA REFORZADA, BOMBO
 CON 3 PALAS MEZCLADORAS DOBLES SOLDADOS
 OUVERTURE RENFORCÉE
 3 PALES DOUBLES DE MALAXAGE MÉCANO-SOUDÉE
 VERSTÄRKTÉ ÖFFNUNG
 TROMMEL MIT 3 GESCHWEIßTE DOPPEL-MISCHSCHAUFELN
 DRUM WITH REINFORCED OPENING
 3 DOUBLE MIXING BLADES

TIMON COM GANCHO DE ENGATE HOMOLOGADO
 TIMON CON GANCHO DEL REMOLQUE HOMOLOGADO
 TIMON HOMOLOGUÉ DOUBLE POSITION
 HOMOLOGIERTE ANKUPPLUNG
 TYPE APPROVED TOW HOOK

2 ROLAMENTOS CÔNICOS
 3 ROLAMENTOS TRANSMISSÃO
 2 RODAMIENTOS CÔNICOS
 3 RODAMIENTOS TRANSMISION
 2 ROULEMENTS CONIQUES SUR L'AXE DE CUVE
 ET 3 ROULEMENTS SUR L'AXE DU PIGNON
 2 KONISCHE LAGER
 3 GETRIEBELAGER
 2 CONICAL BEARINGS
 3 TRANSMISSION BEARINGS

PROTEÇÃO DE CREMALHEIRA OPCIONAL
 PROTECCIÓN DE RACK OPCIONAL
 PROTECTION DE LA COURONE EN OPTION
 ZAHNRADSCHUTZ ALS OPTION
 OPTIONAL GEAR RING PROTECTION



500 4R

400 4R

DOSAGEM CAPACIDAD DOSAGE DOSIERUNG DOSAGE	 2 x 50 Kg + 25 Kg	35 Kg + 35Kg
SEM MOTOR SIN MOTOR SANS MOTEUR OHNE MOTOR WITHOUT ENGINE	 270 Kg	236 Kg
PRODUÇÃO HORÁRIA PRODUCCIÓN HORARIA PRODUCTION HORAIRES STUNDENPRODUKTION PRODUCTION PER HOUR	 3,30 m3/h	2,60 m3/h
TOTAL BALDE MÁX. DEL BOMBO CAPACITÉ DE LA CUVE TROMMELINHALT DRUM CAPACITY	 490 L	360 L
MÁX. DE MISTURA MÁX. DE MEZCLA MAX DE MALAXAGE MISCHLEISTUNG MAX. MIXING	 430 L	330 L
DIMENSÕES DIMENSIONES DIMENSIONS DIMENSIONEN	 1820 x 1100 x 1650 mm	1800 x 1100 x 1600 mm

CAPACIDADES E MEDIDAS PODERÃO TER UMA VARIAÇÃO SUPERIOR A 10%. CAPACIDADES Y MEDIDAS PUEDEN TENER UNA VARIACIÓN SUPERIOR A 10%.
 CAPACITÉS ET MESURES PEUVENT AVOIR UNE VARIATION DE 10% OU PLUS. DIE ANGEDEBEN MASSEN KÖNNEN MEHR ALS 10% ABWEICHEN
 CAPACITY AND DIMENSIONS MAY VARIATE ABOUT 10% OR MORE

OPÇÃO OPCIÓN OPTION OPTION OPTION



CONTA HORAS
 CONTA HORAS
 COMPTEUR D'HEURES
 STUNDENZÄHLER
 HOUR METER



ARRANQUE ELÉCTRICO
 ARRANQUE ELÉCTRICO
 DÉMARRAGE ÉLECTRIQUE
 ELEKTRO STARTER
 ELECTRIC STARTER



SIRL 3,0 hp
 500 4R

SIRL 2,0 hp
 400 4R



SIRL KM173F
 3,8 hp

KOHLER 15LD 225
 4,5 hp

KOHLER KD15-350
 7,0 hp



HONDA GX 160
 5,5 hp

BRIGGS & STRATTON CR 950
 6,5hp



Robin EX 17
 5,7 hp

KOHLER SH265 E16
 6,5 hp

GASOLINA GASOLINA ESSENCE BENZIN PETROL