

Overview of the new STIHL electric chain saws



- High-performance electric motor
- Long service life
- Ergonomic soft grip
- Stable bumper spike
- STIHL QuickStop Super chain brake
- Quick Chain Tensioning requiring no tools
- Transparent oil tank
- Intelligent overload protection
- Practical cable strain relief

	MSE 170 C-Q	MSE 170 C-BQ	MSE 190 C-Q	MSE 190 C-BQ	MSE 210 C-BQ	MSE 230 C-BQ
Rated voltage (V)	230	230	230	230	230	230
Power consumption (kW)	1,7	1,7	1,9	1,9	2,1	2,3
Weight (kg)*	4,2	4,3	4,4	4,5	4,6	4,7
Rollomatic E guide bars** (Bar length, cm)	30/35	30/35	30/35	30/35	35/40	35/40
Sound pressure level*** (dB(A))	92,0	92,0	92,0	92,0	93,0	93,0
Sound power level*** (dB(A))	103,0	103,0	103,0	103,0	104,0	104,0
Vibration level left/right*** (m/s ²)	2,9/3,4	2,9/3,4	2,9/3,4	2,9/3,4	3,4/4,2	3,4/4,2
Cable length (m)	0,4	4,0	1,8	4,0	4,0	4,0
Oilomatic saw chain Pitch Type	3/8" P PMM3 ^①	3/8" P PMM3 ^①	3/8" P PM3 ^②	3/8" P PM3 ^②	3/8" P PM3 ^②	3/8" P PM3 ^②
Soft grip	●	●	●	●	●	●
Lightweight guide bar	○	○	○	○	○	○
Side-mounted chain tensioning	●	—	●	—	—	—
STIHL Quick Chain Tensioning (B)	—	●	—	●	●	●
QuickStop Super chain brake (Q)	●	●	●	●	●	●
Toolless fuel cap	●	●	●	●	●	●

* Without cable, with guide bar and saw chain, without chain oil

** Depending on the type of chain saw, the stated bar length may not equal the actual bar length

*** K factor according to Dir. 2006/42/EC = 2.5 dB(A)

**** K factor according to Dir. 2006/42/EC = 2 m/s²

① PMM3: Picco Micro Mini 3

② PM3: Picco Micro 3

● Fitted as standard

○ Can be retrofitted (special accessory)