

[News](#)
[About Us](#)
[Products](#)
[Application](#)
[Contact Us](#)

[English](#)
[繁體中文](#)

[Member Area](#)

Member ID
Password
[\[Forgot Password \]](#) [\[Register \]](#)

PRODUCTS

[Coil Nailer](#)
[Angle Nailer](#)
[Stapler](#)
[Finish Nailer / F Nailer](#)
[Concrete Nailer](#)
[Pinner](#)
[Rear Exhaust Nailer](#)
[Corrugate Nailer](#)
[Combi Nailer/stapler](#)
[PICTURE FRAME V Nailer](#)
[Carton stapler](#)
[Plier/ manual plier](#)
[C Ring/D Ring](#)
[Clinch Clip](#)
[Decorative Nailer](#)
[Special Nailer](#)
[Electric Nailer](#)
[Cordless Nailer](#)
[foot carton stapler](#)
[Manual Staple Tacker](#)
[Hammer tacker](#)
[TENSIONER](#)
[Air Screw Driver](#)
[Air spray gun](#)
[Air Die Grinder](#)
[Air Grinder](#)
[Air Belt Sander](#)
[Air Micro Die Grinder](#)
[Air Sander](#)
[air saw](#)

C Ring/D Ring

Products >> C Ring/D Ring >> SC7C

SC7C

SC7C C-ring tool, Hog Ring crown:23.9mm shank:1.8mm Closure size:4.8-8.7mm

BRIEFDETAILS

[Operation manual PDF download](#)

SC7C C-ring tool, Hog Ring
crown:23.9mm shank:1.8mm
Closure size:4.8-8.7mm

Feature and Benefits:

- the pusher spring of aplus that can keep long term. Some famous tool that is easy broken on pusher spring
- Aplus tool can fire until the fastener is empty. Another tool will keep 3 or 4 pcs fastener
- Aplus tool can fix fastener on nose.
- As the tool used some time, the fastener is easy take off from nose. Aplus use spring to fix fastener on nose, it can keep fastener.

Application:

- Automotive Seating,
- Auto Control Cables,
- Upholstery, Bagging, Bungee,
- Bedding - Ticking to Inner Spring/Border Wire,
- Pocketed Coils, Caging, Insulation,
- Silt Fence, Rope Tying

Compatible Model:

- Bostitch SC7C, Meiho

Nail specification


	Crown (mm)	Shank Height (mm)	Shank Dia (mm)	Closure Size (mm)
SC7C	23.9	12	1.8	4.8 - 8.7

23.9
12
4.8 Min 8.7 Max
Closure Size


Tool specification

[· Air Tapping](#)
[· Air Ratchet Wrench](#)
[· Air Impact Wrench](#)
[· Air Drill](#)
[· Air Riveter/Riveting Nut](#)
[· impact wrench\(Others\)](#)
[· SPRING BALANCER](#)
[· Coupler and Plug](#)
[· Air Hose](#)
[· REGULATOR](#)
[· Surface Conditioning Disc](#)
[· sanding paper / PAD](#)
[· SCREWDRIVER BITS](#)
[· Impact Socket](#)
[· Impact Socket accessories](#)
[· Impact Socket Set](#)
[· INDUSTRIAL TOOL BOX](#)
[· Air Compressor](#)
[· oil free air compressor](#)
[· Coil Nail](#)
[· C Ring / D Ring](#)
[· Clinch Clip](#)
[· staple/carton staple, coil carton staple](#)
[· Nail / Concrete Nail / PIN](#)
[· carton staple, coil carton staple](#)
[· Framing Nailer](#)
[· V Nail / back nail / Corrugated Nail](#)
[· PDF file](#)

Dimensions (mm) (HxWxL)	Load Capacity (pcs)	Weight (kg)	Driving Power (7kg/cm ²)
374 x 87 x 187	100	1.45	



For C1524G C-Ring


[\[Back \]](#)
[\[Go Top \]](#)


Visitors

On-Line: 3

Visitors: 302934