

KLL 2-20 (606166000) Cross Line Laser
Cardboard box

Order no. 606166000
EAN 4007430284587



Product may differ from Image

- Handy, robust device with impact-proof housing and soft grip material
- Self-levelling thanks to pendulum technology
- Positioned directly against the wall, the laser generates an almost 360° vertical line
- Protection and transport function: Laser in U-frame can be pivoted by 360° to protect the laser optics and pendulum
- Extendible foot for appropriate height adjustment of the laser
- Variable use of the laser: on the floor, mounted on a tripod, fastened to metal with magnet or fixed with metal lugs
- Rare earth magnet with V-groove for stable placement on metallic objects
- Energy-saving power controls for each individual laser line
- LED display advises low energy level in advance

Technical data

Characteristics

Laser class	2
Wavelength	635 nm
Light output	< 1 mW
Laser visibility in indoor areas	20 m / 66 ft
Levelling accuracy	± 0.3 mm/m / ± 0.1875 " over 50 ft
Self-levelling range	± 4.5 °
Straightness of lines	± 0.2 mm/m / ± 0.125 " over 50 ft
Operating time per battery charge	20 h
Protection type IP	IP 54
Weight (with batteries)	0.54 kg / 1.19 lbs
Laser functions	Line function, horizontal / Line function, vertical / Plumb-line function
Number of lines	2
Number of points	2
Tripod thread	1/4"

Scope of delivery

Target plate
3 Batteries AA 1.5 V (LR6)
Belt pouch
Wall bracket