

EX 118



ADJUSTABLE POSITIONNING LANYARD VIA TENSIONER + 1 AM010

Ref. EX118



Product specifications

Adjustable work positioning lanyard via stainless steel tensioner. Adjustable length. Stranded rope Ø 14 mm equipped with a wear indicator. Thimble loop. Splice protection. Protective sheath. 1 hook.

Lanyard: Polyester.

Tensioner: Stainless steel.

COLOUR

Orange

SIZE

0.20 → 2 m, 0.20 to 4 m

Product Use - Risks



Fall



Agriculture / Green areas
craftman



Construction / Civil engineering



Second work /



Heavy industry



Light industry



Oil / Gas



Mining



Wind energy



Work positioning



Restraint

Product's highlights & user's benefits

Recommended accessory for the proper use
of this product : 1 connector AM002

Certifications and Standards



REGULATION (EU) 2016/425

EN363 : 2008 Personal fall protection equipment - Personal fall protection systems

EN364 : 1992 Personal protective equipment against falls from a height : Test method

EN365 : 2004 Personal protective equipment against falls from a height – General requirements for the instructions for use, maintenance, periodic examination, repair, marking and packaging.

EN358 : 1999 Personal protective equipment for work positioning and prevention of falls from a height – Belts and lanyards for work positioning or restraint.

References

References	Bar code	COLOUR	SIZE		
EX118200A	3295249176785	Orange	0.20 → 2 m	5	-
EX118400A	3295249176792	Orange	0.20 to 4 m	5	-