

Hot water high-pressure
cleaners

Montigo LP



Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (three phase models).
- Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve.
- Low voltage and delayed Total Stop.
- Suction and delivery S. S. valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Detergent built-in tank for indirect suction.
- Auxiliary motor for burner.
- Hose reel with brake (**optional**).

Standard equipment:



3.700.0030



3.701.0015



3.103.0050 - mod. 1211

3.103.0048 - mod. 1611



4.618.0049 - 8 m. - mod. 1211

4.618.0143 - 10 m. - mod. 1611

Optional:

- Hose reel with brake (optional) hose not included code 6.608.0073



	Montigo 1211 LP	Montigo 1611 LP
Code	8.630.0105	8.630.0106
Operat. pressure bar	120 (max 150)	160
Operat. pressure psi	1740	2320
Delivery rate l/h	660	660
Temp. max	140°C	140°C
Power ass. W	3000	4300
RPM	1450	1450
Voltage	230 V~50 Hz	400 V~50 Hz