PUNCHERS & BENDERS



■ Model No. **HYBN-120**

Height: 360 mm Weight: 15.8 kgs

■ Specifications:

Max.Pressure: 700 bar Oil Required: 124 cc

Max Output: 21,9 tons / 215 kN

Effective stroke: 120 mm

■ Bending Capacity:

Max. Width : 120 mmMax. Angle : 90 degreeMax. Thickness : 12 mm

• Bending materials: Aluminum, Copper

■ Features:

- Vertical stand ideally suited for bending solid copper and aluminum bus bars.
- 2 lateral parallel-stops fo exact angular positioning of bus bars.
- Convenient scale for reading the current bending angle.
- Single action cylinder can be uncoupled from the bending unit.
- The cylinder can also be connected to our bus bar cutting model HYBC-120.
- Operated by any hydraulic pump with rated oil pressure of 700 bar (10,000 psi).

■ Model No. DBBN-120

Height: 360 mm Weight: 15.8 kgs

■ Specifications:

Max. Pressure: 700 bar Oil Required: 124 cc

Max Output: 21.9 tons / 215 kN

Effective stroke: 120 mm

■ Bending Capacity:

Max. Width: 120 mmMax. Angle: 90 degreeMax. Thickness: 12 mm

• Suitable materials : Aluminum, Copper

■ Features:

- Vertical stand ideally suited for bending solid copper and aluminum bus bars.
- 2 lateral parallel-stops fo exact angular positioning of bus bars.
- Convenient scale for reading the current bending angle.
- Single action cylinder can be uncoupled from the bending unit.
- The cylinder can also be connected to our bus bar cutting model HYBC-120.
- Operated by any hydraulic pump with rated oil pressure of 700 bar (10,000 psi).

