

G Series

Medium Capacity, Single Stage Regulators



G Series regulators use a combination of colours on the gauge face to provide clarity for reading needle position, while a scale and red tick mark indicate actual service pressure of the regulator.

A high-strength zinc aluminium bonnet nearly twice the yield strength of forged brass provides exceptional durability, and ergonomic colour-coded knobs indicate gas type and offer improved comfort when adjusting gas pressure.

- Forged brass body with high strength zinc-aluminium bonnet.
- Long length stem fits all common cylinder valves and allows use with cylinders fitted with a protective cowl.
- Large, clear scale gauges with colour coded operational guidelines, and colour coded PA knobs for ease of use and clear identification of gas type
- Meets ISO 2503
- Date stamped for ease of inspection and replacement

Visit **esab.com** for more information.

Industry

- Shipbuilding
- Automotive
- Rail
- Fabrication
- Offshore
- Construction
- Maintenance/Repair

XA00177420



Technical Data

Model	Gas Service	Gas Pressure	Inlet & Outlet	Inlet Position
G250 S/S OXY S/E 10 Bar	Oxygen	10 bar	5/8" BSP inlet 3/8" BSP outlet RH	Side
G250 S/S OXY 10 Bar	Oxygen	10 bar	5/8" BSP inlet 3/8" BSP outlet RH	Bottom
G250 S/S OXY PLUG 10 Bar	Oxygen	10 bar	5/8" BSP inlet 3/8" BSP outlet RH	Bottom
G250 S/S ACET S/E 1.5 Bar	Acetylene	1.5 bar	5/8" BSP inlet 3/8" BSP outlet LH	Side
G250 S/S ACET 1.5 Bar	Acetylene	1.5 bar	5/8" BSP inlet 3/8" BSP outlet LH	Bottom
G250 S/S ACET PLUG 1.5 Bar	Acetylene	1.5 bar	5/8" BSP inlet 3/8" BSP outlet LH	Bottom
G250 S/S PROP PLUG S/E 0-4 Bar	Propane	4 bar	5/8" BSP inlet 3/8" BSP outlet LH	Side
GF250 S/S AR/CO2 40LPM	Argon / CO ₂	0-40 l/min	5/8" BSP inlet 3/8" BSP outlet RH	Bottom
GF250 AR/CO2 S/E 40 LPM	Argon / CO ₂	0-40 l/min	5/8" BSP inlet 3/8" BSP outlet RH	Side
G250 S/S ARGON/CO2, PRESET	Argon / CO ₂	2 bar	5/8" BSP inlet 3/8" BSP outlet RH	Bottom
G250 S/S ARGON/CO2, S/E PRESET	Argon / CO ₂	2 bar	5/8" BSP inlet 3/8" BSP outlet RH	Side
G250 S/S PROP S/E 0-4 Bar	Propane	4 bar	5/8" BSP inlet 3/8" BSP outlet LH	Side
G250 S/S OXY 4 Bar	Oxygen	4 bar	5/8" BSP inlet 3/8" BSP outlet RH	Bottom
G250 S/S OXY S/E 4 Bar	Oxygen	4 bar	5/8" BSP inlet 3/8" BSP outlet RH	Side
GF250 AR/CO2 S/E, NEVOC 40 LPM	Argon / CO ₂	0-40 l/min	NEVOC inlet 3/8" BSP outlet RH	Side
G250 S/S INERT, S/E 10 Bar	Inert	10 bar	5/8" BSP inlet 3/8" BSP outlet RH	Side

Ordering Information

Model	Description	Part Number
G250 S/S OXY S/E 10 Bar	10 Bar Oxygen Regulator, Side Entry	0700017204
G250 S/S OXY 10 Bar	10 Bar Oxygen Regulator, Bottom Entry	0700017205
G250 S/S OXY PLUG 10 Bar	10 Bar Oxygen Regulator, Bottom Entry (Plugged)	0700017206
G250 S/S ACET S/E 1.5 Bar	1.5 Bar Acetylene Regulator, Bottom Entry	0700017210
G250 S/S ACET 1.5 Bar	1.5 Bar Acetylene Regulator, Side Entry	0700017211
G250 S/S ACET PLUG 1.5 Bar	1.5 Bar Acetylene Regulator, Bottom Entry (Plugged)	0700017212
G250 S/S PROP PLUG S/E 0-4 Bar	4 Bar Propane Regulator, Side Entry (Plugged)	0700017213
GF250 S/S AR/CO2 40LPM	Flow Gauge Regulator, Bottom Entry	0700017221
GF250 AR/CO2 S/E 40 LPM	Flow Gauge Regulator, Side Entry	0700017222
G250 S/S ARGON/CO2, PRESET	2 Bar Preset Flow Gauge Regulator, Bottom Entry	0700017223
G250 S/S ARGON/CO2, S/E PRESET	2 Bar Preset Flow Gauge Regulator, Side Entry	0700017460
G250 S/S PROP S/E 0-4 Bar	4 Bar Propane Regulator, Side Entry (Single Gauge)	0700017458
G250 S/S OXY 4 Bar	4 Bar Oxygen Regulator, Bottom Entry	0700017459
G250 S/S OXY S/E 4 Bar	4 Bar Oxygen Regulator, Side Entry	0700017461
GF250 AR/CO2 S/E, NEVOC 40 LPM	Flow Gauge Regulator, Side Entry, NEVOC	0700018107
G250 S/S INERT, S/E 10 Bar	10 Bar Inert Gas Regulator, Side Entry	0700018108

XA00177420 / 2016-07-06 / ESAB reserves the right to alter specifications without prior notice



ESAB / esab.com



COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =