

## PD8045

13 Gauge grey ANSI Cut Level A4/ ISO13997  
Cut Level D shell Grey PU coating on palm

### Description

- The lightweight liner with ISO Cut Level D (ANSI Level 4) performance for the ultimate in cut resistance.
- The comfortable and flexible plaited liner also features an optimized lycra content that is soft and cool on the skin for all-day comfort.
- The palm-dipped polyurethane (PU) coating provides enhanced grip in dry and light oil environments for secure handling and offers EN Abrasion Level 4 (ANSI Level 6) for extended glove life. The PU coating is also to protect the quality of industrial finishing processes.

**OEKO-TEX®**  
CONFIDENCE IN TEXTILES  
**STANDARD 100**  
17.HCN.29929 HOHENSTEIN HTTI  
Tested for harmful substances.  
[www.oeko-tex.com/standard100](http://www.oeko-tex.com/standard100)


### Product details and Packing



<b>ANTISTATIC</b>	NO
<b>AVAILABLE SIZES</b>	8,9,10
<b>COATING COLOR</b>	GRAY
<b>COATING MATERIAL</b>	POLYURETHANE
<b>CONSTRUCTION</b>	KNITTED
<b>CUFF STYLE</b>	KNITWRIST
<b>FINISHING</b>	PALM COATED
<b>GAUGE</b>	13
<b>LATEX FREE</b>	YES
<b>LINER COLOR</b>	GRAY
<b>LINER MATERIAL</b>	HPPE
<b>WASHING TEMPERATURE</b>	40 °C (104 °F)

### FEATURES

- ✓ Strong fibers provide excellent resistance to cuts and burrs.
- ✓ Resilient coating resists abrasions and extends glove life.
- ✓ High level of cut protection (ANSI Level 4)



### Standards

CE EN388: 4X43D

EN 388



4X43D

### Application

- Press shop operations
- Handling parts with sharp, rough edges
- Handling structural and body components
- Chassis assembly, body trimming

### Packaging

12 bags / carton



x12



x12

