

PETRO VE766



FULL PVC COATING ON JERSEY LINER GLOVE - LENGTH 62CM

Model VE766



Product specifications

Chemical PVC. PVC on cotton knitted lining gauge 13. Rough-textured hand. Length: 62 cm. Thickness: 1.30 mm.

Support: cotton.
Coating: PVC.
Thickness: 1,30 mm.

COLOUR

Blue

SIZE

08, 09, 10

Product Features and Benefits



0%
SILICONE
LATEX



Textured structure

Good grip of handled objects

PVC

Good resistance to abrasion
Material very resistant to oils, chemicals and
petroleum derivatives

Length : 62 cm

Complete arm protection

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

4: Resistance to abrasion (from 1 to 4)

1: Resistance to cutting (from 1 to 5)

3: Resistance to tear (from 1 to 4)

1: Resistance to puncture (1 to 4)

X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro- organisms - Part 1: Terminology and performance requirements for chemical risks.

TYPE B: Type B - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 3 chemicals at level 2 according to EN16523-1: 2015 (from 1 to 6).

.. Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.

J 2 > 30 mn: n-Heptane (J) CAS 142-85-5

K 6 > 480 mn: Caustic soda 40% (K) CAS 1310-73-2

L 4 > 120 mn: Sulphuric acid 96 % (L) CAS 7664-93-9



EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro- organisms risks.

BACTERIA + FUNGI .. BACTERIA + FUNGI : Water and air tightness according to EN ISO 374-2:2019.



Item details

Item details	Bar code	COLOUR	SIZE		
VE766BL08	3295249196141	Blue	08	60	6
VE766BL09	3295249196158	Blue	09	60	6
VE766BL10	3295249196165	Blue	10	60	6