

■ Model No. **HD-BGD3 / HD-OD3**

Length: 652 mm
Weight: 3.20 kgs
Packaging: Box

■ Crimping Capacity:

- Crimping Force: 4.5 ton
- Uses W-style dies.
- Storage carrying case & dies are sold separately.

■ Features:

- Proper crimps are assured with butting steel jaws.
- Increased strength and greater bearing area is provided with larger steel bolts.
- Fast, easy, one-hand die insertion.
- No lost dies with spring loaded positive lock die retainer buttons.
- Full crimp force assured with over center cam action.
- Operator protection provided with butt stops and heat shrink tubing.
- Long life expectancy provided with fiberglass handles and light weight high strength aluminum alloy castings.
- The "D3" groove accommodates the line of type "W"-die inserts.



■ Model No. **CASE-OD3**

■ Connector Range:

- Copper, Aluminum, ACSR, Copperweld, Alumoweld, Steel, 6201, 5005, Compressed and Compact conductors.
- Copper Taps: # 10 sol.-2/0 str.
- Aluminum, ACSR Taps: # 14 sol. -4/0 ACSR
- Stirrups: # 6 ACSR-4/0 ACSR
- Overhead Full Tension Deadend, Full Tension Splices, Non Tension Splices, and Terminals Conductor Range: # 10 str. -4/0 ACSR
- Code conductor connectors: # 6-4/0 str. Copper and Aluminum

KuDos KW-dies	KW-BG	KW-O	KW-C	KW-K840	KW-161	KW-162	KW-163	KW-164
Burndy W-Dies	W-BG	W-O	W-C	W-K840	W-161	W-162	W-163	W-164

KuDos KW-dies	KW-165	KW-166	KW-171	KW-237	KW-243	KW-247	KW-249	KW-702
Burndy W-Dies	W-165	W-166	W-171	W-237	W-243	W-247	W-249	W-702

