



**Chicago
Pneumatic**



CPRX
Piston compressors

People. Passion. Performance.

ONE STAGE BELT DRIVE
CPRX Series 1,5-3 kW / 2-4 hp

Join thousands of convinced customers operating millions of CHICAGO PNEUMATIC compressors worldwide



Easy to move



Stability



Simultaneous use



CPRX PAT24A/200 CM3

TWO STAGE BELT DRIVE
CPRX Series 3-7,5 kW / 4-10 hp

For Chicago Pneumatic, it is not just about products. We value our end users' and distributors' performance and do our ultimate best to make it easy to work with us while providing reliable products with passion.

- ✓ Plug and play air solutions
- ✓ Always available and ready to use
- ✓ First class usability



CPRX PAT24A/200 CM3

Model	Tank	F.A.D.		POWER		RPM	VOLT	PRESSURE	dB(A)	L x W x H (mm)	kg
	Lt	l/min	CFM	HP	KW			BAR			
CPRX PAT24/50 CM2 V230	50	255	8,9	2	1,5	1075	230/1	10	93	870 x 370 x 780	49
CPRX PAT24/100 CM2 V230	100	255	8,9	2	1,5	1075	230/1	10	93	1010 x 415 x 900	56
CPRX PAT24A/200 CM3 V230	200	320	11,2	3	2,2	1300	230/1	10	95	1500 x 470 x 1110	91
CPRX PAT38/270 CM3 V230	270	393	13,8	3	2,2	1050	230/1	10	93	1530 x 595 x 1160	138
CPRX PAT38A/270 CM4 V230	270	486	17	4	3	1300	230/1	10	93	1530 x 595 x 1160	138
CPRX PAT38A/270 CT4	270	486	17	4	3	1300	400/3	10	93	1530 x 595 x 1160	138
CPRX PAT38A/150 VM3	V150	393	13,8	3	2,2	1050	230/1	10	93	850 x 970 x 1950	160

One Stage compressors:

CPRX: Model
PAT24 – PAT38: One stage pump design 24 (pump 2-3hp) 38 (3-4hp)
A: After cooler
50 – 100 – 270 – 150: Vessel size in L / V vertical
C: Wheels
M-T: M= Mono phase T= 3 phase
2 – 3 – 4: Motor power in HP

Model	Tank	F.A.D.		POWER		RPM	VOLT	PRESSURE	L x W x H (mm)	kg
	Lt	l/min	CFM	HP	KW			BAR		
CPRX B4900/200 VT4	V200	514	18	4	3	1400	400/3	11	850 x 970 x 1950	180
CPRX B5900B/270 CT5,5 V400	270	653	22,9	5,5	4	1400	400/3	11	1575 x 680 x 1150	170
CPRX B5900B/500 FT5,5 V400	500	653	22,9	5,5	4	1400	400/3	11	2030 x 670 x 1400	219
CPRX B6000/500 FT7,5 V400	500	827	28,9	7,5	5,5	1400	400/3	11	2030 x 670 x 1400	260
CPRX B7000/500 CT10 V400	500	1201	42,4	10	7,5	1300	400/3	11	2030 x 670 x 1400	282
CPRX B7000/500 FT10 V400	500	1201	42,4	10	7,5	1300	400/3	11	2030 x 670 x 1400	279
CPRX B6000/500 T7,5 V400	500	1654	57,9	7,5+7,5	5,5+5,5	1400	400/3	11	2030 x 670 x 1400	387
CPRX B6000/900 T7,5 V40	900	1654	57,9	7,5+7,5	5,5+5,5	1400	400/3	11	2070 x 800 x 1570	500
CPRX B7000/900 T10 V400	900	2420	84,7	10+10	7,5+7,5	1300	400/3	11	2070 x 800 x 1570	536
CPRX B7000/1000 T10 V400	1000	2420	84,7	10+10	7,5+7,5	1300	400/3	11	2070 x 800 x 1570	538

Two Stage compressors:

CPRX: Model
B4900-5900-6000-7000: Two stage pump design (4-10hp)
200-270-500-900-1000: Vessel size in L
C-F: C=Wheels F=Stationary
M-T: M= Mono phase T= 3 phase
4-5,5-7,5-10: Motor power in HP

* Our units are also available in 60Hz, please contact your local sales representative for more information

Chicago Pneumatic: full offer, global presence



Industrial & vehicle service tools



Construction tools




Portable compressors and generators



Paving equipment



Industrial compressors



Original parts.
Your quality assurance.

DISTRIBUTED BY

The 'original part' identification confirms that these components passed our strict test criteria. All parts are designed to match the compressor and are approved for use on the specified compressor. They have been thoroughly tested to obtain the highest level of protection, extending the compressors' lifetime and keeping the cost of ownership to an absolute minimum. No compromises are made on reliability. The use of 'original part' certified quality components helps ensure reliable operation and will not impact the validity of your warranty, unlike other parts. Look for your quality assurance.

www.cp.com