

HAMMERS AND BREAKERS

HYDRAULIC HAMMER AND BREAKERS	BRK 40 VR	BRK 55 VR	BRK 70 VR	BRK 95 VR
Weight including Hoses kg (lb)	25 (55)	28 (62)	32.5 (71.5)	39 (86)
Length mm (in)	650 (25.5)	690 (27)	765 (30)	765 (30)
Oil Flow l/min (gpm)	20 (5)	20–30 (5–8)	20–30 (5–8)	30–40 (8–11)
Working Pressure bar (psi)	95–110 (1,375–1,595)	105–125 (1,525–1,815)	110–125 (1,595–1,815)	110–125 (1,595–1,815)
Maximum Back Pressure bar (psi)	10 (145)	15 (220)	15 (220)	15 (220)
Impact Rate bpm	1,400	1,500–2,100	1,350–1,750	1,150–1,600
Vibration Level 3 Axes* (ISO 28927–10) m/s ²	5	4.6	4.6	5.4
Sound Power Level Guaranteed* (2000/14/EC) Lw dB(A)	106	107	107	106
Sound Pressure Level* (ISO 11203) (Lp, r=1m) dB(A)	93	95	94	93
EHTMA Class	C	C/D	C/D	C/D
Part Numbers				
Chuck Size Hex 22 x 82.5 mm (7/8 x 3-1/4 in)	–	–	–	–
Chuck Size Hex 25 x 108 mm (1 x 4-1/4 in)	1801 3447 19	1801 3547 23	–	–
Chuck Size Hex 28 x 152 mm (1-1/8 x 6 in)	1801 3447 20	–	–	–
Chuck Size Hex 28 x 160 mm (1-1/8 x 6-1/4 in)	–	1801 3547 31	–	1801 3747 30
Chuck Size Hex 32 x 152 mm (1-1/4 x 6 in)	1801 3447 21	–	1801 3647 27	–
Chuck Size Hex 32 x 160 mm (1-1/4 x 6-1/4 in)	1801 3447 22	1801 3547 25	1801 3647 28	1801 3747 30

HYDRAULIC HAMMER AND BREAKERS	BRK 25 D 
Weight including Hoses kg (lb)	15.5 (34)
Length mm (in)	650 (25.5)
Oil Flow l/min (gpm)	20 (5)
Working Pressure bar (psi)	80–100 (1,160–1,450)
Maximum Back Pressure bar (psi)	10 (145)
Impact Rate bpm	2,300
Vibration Level 3 Axes* (ISO 28927–10) m/s ²	16.5
Sound Power Level Guaranteed* (2000/14/EC) Lw dB(A)	105
Sound Pressure Level* (ISO 11203) (Lp, r=1m) dB(A)	92
EHTMA Class	C
Part Numbers	
Chuck Size Hex 22 x 82.5 mm (7/8 x 3-1/4 in)	1801 1746 12

*BRK 25 D measured at 20 l/min.



BRK 25 D

Applications:

- Horizontal work in renovation
- Demolition
- Structural alterations

Key features:

- High impact power
- 2,300 blows/min
- Standard D-handle
- Optional detachable front handle
- 360° pivot