



HEAVY BREAKERS

Pneumatic Breakers	CP 1260	CP 1260 S	 CP 1260 SVR	CP 1290	CP 1290 S	 CP 1290 SVR
Weight kg	29	31	34	37	39	43.5
Length mm	680	680	735	730	730	785
Air Consumption l/s	34.5	34.5	34.5	43	43	43
Blows Per Minute bpm	1,300	1,300	1,300	1,100	1,100	1,100
Vibration Level 3 Axes*** (ISO 20643) m/s ²	20.7	20.7	6.5	18.4	18.4	6.2
Sound Power Level Guaranteed (I2000/14/EC) dB(A)	–	110	110	–	111	111
Sound Pressure Level (ISO 11203) dB(A)	–	97	97	–	98	98
Air Inlet	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF
Part Number Chuck: 28 x 160 mm*	8900 0030 29	8900 0030 31	8900 0030 33	8900 0030 38	8900 0030 40	8900 0030 42
Part Number Chuck: 32 x 160 mm**	8900 0030 28	8900 0030 30	8900 0030 32	8900 0030 37	8900 0030 39	8900 0030 41

* Also for 28 x 152

** Also for 32 x 152 mm

All values at 6 bar. Air inlet thread is NPTF 3/4". Claw couplings for BSP 3/4" and G 3/4" can also be used on this thread. The breakers are delivered without claw couplings.

Please Note: Non-muffled tools are not CE-marked and must not be sold for use in the EEA (European Economic Area), i.e. EU plus Norway, Iceland and Lichtenstein.

Pneumatic Breakers	CP 0117	CP 0117 S
Weight kg	35	36
Length mm	740	740
Air Consumption l/s	35	35
Blows Per Minute bpm	1,080	1,080
Vibration Level 3 Axes*** (ISO 20643) m/s ²	–	11.9
Sound Power Level Guaranteed (I2000/14/EC) dB(A)	–	108
Sound Pressure Level (ISO 11203) dB(A)	–	95
Air Inlet	3/4" NPTF	3/4" NPTF
Part Number Chuck: 28 x 160 mm*	8900 0030 47	8900 0030 49
Part Number Chuck: 32 x 160 mm**	8900 0030 48	8900 0030 50

* Also for 28 x 152

** Also for 32 x 152 mm

All values at 6 bar. Air inlet thread is NPTF 3/4". Claw couplings for BSP 3/4" and G 3/4" can also be used on this thread. The breakers are delivered without claw couplings.

Please Note: Non-muffled tools are not CE-marked and must not be sold for use in the EEA (European Economic Area), i.e. EU plus Norway, Iceland and Lichtenstein