

HAMMERS AND BREAKERS

HYDRAULIC HAMMER AND BREAKERS	BRK 70 VR
Weight including Hoses kg (lb)	32.5 (71.5)
Length mm (in)	765 (30)
Oil Flow l/min (gpm)	20–30 (5–8)
Working Pressure bar (psi)	110–125 (1,595–1,815)
Maximum Back Pressure bar (psi)	15 (220)
Impact Rate bpm	1,350–1,750
Vibration Level 3 Axes* (ISO 28927–10) m/s ²	4.6
Sound Power Level Guaranteed* (2000/14/EC) L _w dB(A)	107
Sound Pressure Level* (ISO 11203) (L _p , r=1m) dB(A)	94
EHTMA Class	C/D
Part Numbers	
Chuck Size Hex 22 x 82.5 mm (7/8 x 3-1/4 in)	–
Chuck Size Hex 25 x 108 mm (1 x 4-1/4 in)	–
Chuck Size Hex 28 x 152 mm (1-1/8 x 6 in)	–
Chuck Size Hex 28 x 160 mm (1-1/8 x 6-1/4 in)	–
Chuck Size Hex 32 x 152 mm (1-1/4 x 6 in)	1801 3647 27
Chuck Size Hex 32 x 160 mm (1-1/4 x 6-1/4 in)	1801 3647 28



BRK 70 VR

Applications:

- Heavier jobs in tough materials such as asphalt, frozen soil and reinforced concrete

Key features:

- Best-in class power to weight ratio
- Can be used with both 30 l/min and 20 l/min power packs