

## TER300



HEAT-RESISTANT COWHIDE WELDER'S GLOVE

Model TER300



### Product specifications

Heat-resistant cowhide split leather palm (HR). Leather reinforcement on palm. Cotton lined hand and cuff. Kevlar® Technology sewn. American assembly. Length: 40 cm.

Heat-resistant treated split cowhide leather. Thickness > 1.2 mm for each layer.

Cuff lining: Cotton 270 g/m<sup>2</sup>.

Hand lining: Cotton 160 g/m<sup>2</sup>.

Kevlar® thread.

#### COLOUR

Blue-Yellow

#### SIZE

09, 10

## Product Features and Benefits



The construction of the glove in superposition of layers

Protection against the effects of contact heat



Kevlar® thread stitching

Self-extinguishing

THT treated heat resistant leather

Decreased responsiveness to flames  
High flexibility of the leather

## Certifications and Standards



REGULATION (EU) 2016/425

**EN ISO 21420:2020 General requirements**

1: Dexterity (from 1 to 5)

**EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)**



3: Resistance to abrasion (from 1 to 4)

1: Resistance to cutting (from 1 to 5)

4: Resistance to tear (from 1 to 4)

4: Resistance to puncture (1 to 4)

X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

**EN407: 2020 Protective gloves against Heat & Fire risks (X = Unrealized test)**



4: Flame spread resistance.

3: Contact heat resistance (from 1 to 4)

3: Convective heat resistance (1 to 4)

1: Radiant heat resistance (from 1 to 4)



4: Small splashes of molten metal (from 1 to 4)

X: Large quantities of molten metal (from 1 to 4)

**EN12477:2001/A1:2005 Protective gloves for welders**

TYPE A: Welding - Other welding processes - less dexterity - Type A

## Item details

| Item details | Bar code      | COLOUR      | SIZE |  |  |
|--------------|---------------|-------------|------|---|---|
| TER30009     | 3295249254933 | Blue-Yellow | 09   | 60  | 6   |
| TER30010     | 3295249254674 | Blue-Yellow | 10   | 60  | 6   |