

CP MOTOR
DRILLS AND BREAKERS

CP ROAD

Weight kg (lb)	22 (48.5)
-----------------------	-----------

Length mm (in)	743 (29.3)
-----------------------	------------

Impact Energy J (ft-lb)	60 (44)
--------------------------------	---------

Blow Frequency bpm	1,440
---------------------------	-------

Power kW	2
-----------------	---

Motor cc	90, 2-stroke
-----------------	--------------

Fuel Capacity l (gal)	1.0 (0.22)
------------------------------	------------

Fuel Mix %	2
-------------------	---

Fuel Consumption l/hour (gal/hour)	0.9 (.19)
---	-----------

Alkylate Fuel	Yes
----------------------	-----

Vibration Levels 3-Axis (ISO 28927-10 on Dynaload) m/s ² (ft/s ²)*	7.0 (23.0)
--	------------

Sound Power Level (2000/14/) dB(A)*	109
--	-----

Part Number (ISO Standard Shank)

Chuck Size Hex 22 x 108 mm (7/8 x 4-1/4 in)	—
---	---

Chuck Size Hex 25 x 108 mm (1 x 4-1/4 in)	8318 0900 61
---	--------------

Chuck Size Hex 28 x 160 mm (1-1/8 x 6-1/4 in)	—
---	---

Chuck Size Hex 32 x 160 mm (1-1/4 x 6-1/4 in)	8318 0900 21
---	--------------

Part Number (US Shank)

Chuck Size Hex 25 x 108 mm (1 x 4-1/4 in)	8318 0900 29
---	--------------

Chuck Size Hex 28 x 152 mm (1-1/8 x 6 in)	—
---	---

Chuck Size Hex 32 x 152 mm (1-1/4 x 6 in)	—
---	---

* Full details of measurement are available in the Safety and Operating Instruction of the product. It can be found on www.cpprintshop.com

¹⁾ Only available for China

Available from PTD (ISO version) CP Drill Kit: 8318090041, CP Drill with Trolley: 8318090042