# **CRL 50 Misting**

### STANDARD EQUIPMENT





#### Optional:

- 0.966.0078 Hose reel hose included 15 m
- 0.906.0112 Nozzle set for Misting 4 x 020

## **Equipped with:**

• High-strength 50 l. polyethylene tank • Comet AXR misting pump • Single-phase electric induction motor • Very low centre of gravity which ensures stability • Complete emptying including on uneven ground • Lance fasteners • Spray gun GC 251 with swivel + lance provided with special multi-nozzle spraying head • Vertical lance positioning for static use • External filter • Tubular painted-steel frame with detachable handles • Support foot built in the frame, not removable • Puncture-proof tyres

# **SANITIZE BY MISTING**

The most suitable sanitizer for these applications is common hydrogen peroxide, a completely non-toxic and non-corrosive sanitizer but which is extremely effective against viruses and bacteria.

The treatment does not generate the formation of Volatile Organic Compounds and degradation is rapid and reaches over 99.99% in about 20 minutes.

	CRL 50 Misting
code	0.068.0007
operat. pressure max	80 bar-1160 psi
delivery rate	60 l/h-0,26 GPM
power	Electric motor 230V ~ 50Hz
solution tank capacity	50 lt.
high pressure hose	10 m.