

SAGOLA®

4000 SERIES

2013
NEW PRODUCT

This line is designed for paint booths in bodyshop, wood and metal works where the highest finishing is needed.

- > Strong and highly effective design.
- > Easy-to-use, smooth handling.
- > Manufactured with highly durable materials.
- > Long lasting anticorrosion treatment in all surfaces.
- > Automatic draining system.
- > High precision regulators and manometer.
- > Easy-to-maintain.

Great Advantages

High quality filtering.

Valid for Water base and HS.

Quick couplings with stainless steel mechanisms and silicone-free gaskets.

Filtration down to 0.01 microns.

It holds and automatically drains condensed water and oil.



PLUS
VERSION
includes
quick coupling



Made in Spain

www.sagola.com

4120 PURIFYING FILTER + REGULATOR

Effective solution for compressed air filtration in professional paint booths for: car refinish, wood, machinery, plastics and industry in general.

- > Highly reliable air regulation system.
- > Manufactured from a solid aluminum block.
- > It eliminates air, oil and particles.
- > Friction and centrifugal filtration.
- > Automatic drain of condensed liquids.
- > High air flow.
- > High quality manometer.

Code	Version
10 730 501	4120
10 730 502	4120 PLUS (includes coupling)

Dimensions 4120: 279 x 117 x 69,5 mm.
Dimensions 4120 PLUS: 279 x 117 x 96 mm.
Weight: 4120: 1.015 gr. 4120 PLUS: 1.220 gr.
Brass filter: 20 μ (microns)
Drain system: automatic
Air flow: 1.700 l/min.
Maximum pressure: 12 bar
Air inlet: 1/2"
Coupling 4120 PLUS: SAGOLA US Mil



4220 PURIFYING FILTER + REGULATOR COALESCENT FILTER

Two stage air filter. Maximum filtering level.

Recommended for last generation finishes.

Waterborne paints, HS clearcoats and enamels, high gloss lacquers.

- > Highly reliable air regulation system.
- > Manufactured from a solid aluminum block.
- > 1st stage: water, oil and particles filtering
+ 2nd stage: submicronic filtering. 0.01 microns
- > Automatic drain of condensed liquids.
- > High air flow.
- > High quality manometer.

Code	Version
10 750 401	4220
10 750 402	4220 PLUS (includes coupling)

Dimensions 4220: 279 x 117 x 162 mm.
Dimensions 4220 PLUS: 279 x 117 x 186 mm.
Weight: 4220: 1.797 gr. 4220 PLUS: 2.002 gr.
Brass filter: 20 μ + Coalescent filter: 0.01 μ
Drain system: automatic + semiautomatic
Air flow: 1.700 l/min.
Maximum pressure: 12 bar
Air inlet: 1/2"
Coupling 4220 PLUS: SAGOLA US Mil

