



GMAX II 5900 Standard Series Gas Airless Sprayer, Hi-Boy

Part Number: 17E831

Features

Everyday Reliability. Graco GMAX Standard Series gas-powered airless paint sprayers deliver unmatched durability and performance, with the capability to handle the widest range of tip sizes, longer hose lengths and heavier coatings with ease.

- Endurance Chromex Piston Pump
 - The most reliable pump
 - Lasts 2X longer than the next leading brand
 - Repack the pump in minutes with the new QuikPak Cartridge System
 - QuikChange pump design allows you to swap the pump easily on the job
 - Faster cleaning with the QuikAccess intake foot valve
- SmartControl 3.0
 - Consistent spray fan & pressure control
 - Handles the widest range of coatings with the most consistent fan pattern
 - Lowest dead band at any pressure
- Precision Advantage Drive
 - The longest lasting drive
 - Hardened steel gears provide extremely quiet operation
 - Lifetime Warranty
- Easy Out Pump Filter
 - Easy maintenance & less clogging
 - Exclusive inside-out filtering won't collapse to ensure a quality finish
 - Vertical design for less mess

- Heavy-Duty Prime Valve
 - Maintenance-free design withstands high-pressure dumping
- Durable Cart Design
 - Rugged and easy-to-maneuver
 - Thick chrome over steel and pneumatic wheels for tough jobsite conditions
 - Retractable handle doubles as coiled hose storage
- Honda® Engine
 - Reliable, powerful & easy-to-start
 - Oil Alert shuts down engine to prevent damage if oil level drops too low
 - Contractor Preferred
- Contractor PC Spray Gun
 - All-day comfort & control
 - Lightest weight gun in its class
 - Up to 50% lighter trigger pull force
 - E-Z Fit adjustable trigger length
 - Complete gun rebuild in seconds with ProConnect cartridge
 - More info: graco.com/ContractorPC
- Jobsite Ready
 - Includes RAC X SwitchTip and 50 ft of BlueMax II hose

Specifications & Documents

Technical Specifications

Convertible	Non-Convertible
Engine Brand	Honda
Engine Size (HP)	6.5
Features	Endurance Chromex Pump, SmartControl 3.0, Honda Engine, Advantage Drive, Easy Out Filter, Heavy-Duty Prime Valve, Contractor PC Gun
Fluid Inlet Size (in)	1-5/16

Product Manuals

[3A6400B, GMAX 3400, GMAX II 3900/5900/7900, and TexSpray 5900HD/7900HD Airless Sprayers, Operation, English](#)

[3A6417G, GMAX™ 3400, GMAX™ II 3900/5900/7900, and TexSpray 5900HD/7900HD Airless Sprayers, Parts, English](#)

[3A6285K, Manual, Contractor PC Spray Guns, Operation, Parts, Repair, English](#)

[3A6418A, GMAX 3400™, GMAX™ II 3900/5900/7900, and TexSpray 5900HD/7900 HD Airless Sprayer Manuals, Collation, English](#)

Fluid Inlet Thread Type	UN-2A
Fluid Outlet Size (in)	1/4
Fluid Outlet Thread Type	NPSM
Frame Configuration	Hi-Boy
Hose Inlet Diameter (in)	1/4
Includes	Contractor PC Gun, RAC X LP 517 Spray Tip, RAC X Guard, 1/4 in x 50 ft BlueMax II Airless Hose, TSL 4 oz
Inlet Paint Strainer	8 Mesh Stainless Steel Screen
Maximum Flow Rate (GPM)	1.6
Maximum Sound Pressure Level (dB(A))	96
Maximum Tip Size (in)	0.043
Maximum Tip Size 1 Gun (in)	0.043
Maximum Tip Size 2 Guns (in)	0.029
Maximum Tip Size 3 Guns (in)	0.023
Maximum Working Pressure (MPa)	22.8
Maximum Working Pressure (psi)	3300
Model	GMAX II
Number of Guns	3
Outlet Paint Filter	60 Mesh Stainless Steel Screen
Overall Height (in)	40.5
Overall Length (in)	33.0
Overall Width (in)	24.4
Power Rating (HP)	6.5
Power Rating (W)	4847
Power Rating (kW)	4.85
Power Source	Gas
Pressure Control Type	SmartControl 3.0
Product Series	Standard
Pump Mount Type	QuikChange
Pump Rod Type	Chromex
Pump Sleeve Material	Stainless Steel
Pump Type	Endurance

Recommended Annual Usage	Up to 1,000 gallons per week
Series	5900
Type	Airless Sprayer
Weight (lb)	138
Wetted Material	Acetal, Aluminum, Chrome Plating, Fluoroelastomer, Leather, Nylon, PTFE, Polyurethane, Stainless Steel, Tungsten Carbide, UHMWPE, Zinc-Plated Carbon Steel, Nickel-Plated Carbon Steel