

SLOGGING OPEN WRENCHES



The EGA Master Non-sparking slogging open wrenches are designed to tighten or loosen large bolts and nuts with the help of hammer or mallet in potentially explosive environments, such as oil platforms, petrochemicals, shipbuilding, etc.



1. Suitable to be used with hammer or mallet.

2. With a hardness of 311-408 Brinell (Cu-Be) and 241-311 Brinell (Al-Bron).

SLOGGING OPEN WRENCHES MM

COD.	MAT.	COD.	MAT.	AF mm	L (mm)	Kg
70280		71013		14		
70281		71014		17	130	0,1
70282		71015		19		
36466		36467		20		
70283		71016		22		0,2
70284		71017		24	150	
74875		74876		25		
36468		36469		26		0,3
70285		71018		27	170	
74877		74878		28		
77278		77279		29		
70286		71019		30	190	0,4
70287		71020		32		
77280		77281		33		0,5
74847	Cu-Be	74848	Al-Bron	34		0,6
77282		77283		35		
70288		71021		36	210	0,7
77284		77285		37		
74341		74342		38		0,8
70289		71022		41		
77286		77287		42	225	0,9
79089		77778		45		
70290		71023		46	245	1,1
77288		77289		47		1,2
70291		71024		50	270	
77290		77291		52		1,4
77292		77293		54		
70292		71025		55	300	1,5
77294		77295		56		1,8
77296		77297		58	310	2

COD.	MAT.	COD.	MAT.	AF mm	L (mm)	Kg
70293		71026		60		2
77298		77299		63	310	2,4
70294		71027		65		
77300		77301		67	340	2,5
70295		71028		70		3
77302		77303		71	365	
70296		71029		75		3,5
77304		77305		77	375	
71007		71030		80		4
77306		77307		82	395	
71008		71031		85	405	5
77308		77309		88		
71009		71032		90	438	
77310		77311		94		6,5
71010		71033		95	445	
71011	Cu-Be	71034	Al-Bron	100	480	8,5
71012		71035		105	500	10
74849		74850		110	510	
74880		74881		115	520	
77312		77313		120	530	12
74761		74762		125	545	
77314		77315		130	560	
77316		77317		135	575	18
77318		77319		140	585	
77320		77321		145	630	
77322		77323		150	640	24
77324		77325		155		
36470		36471		160	650	37
36472		36473		165		
36474		36475		170		43
36476		36477		175	700	
36478		36479		180		44