


## SLOGGING RING INCH.



| COD   |          | L   | A   | B  | C  | Kg  |   |   |
|-------|----------|-----|-----|----|----|-----|---|---|
| 67369 | 1/2"     | 100 | 24  | 9  | 5  | 0,1 |   |   |
| 67370 | 3/4"     | 145 | 32  | 12 | 7  |     |   |   |
| 67371 | 7/8"     | 155 | 38  | 13 | 8  | 0,2 |   |   |
| 67372 | 15/16"   | 165 | 42  | 14 | 9  |     |   |   |
| 60983 | 1"       | 175 | 46  |    | 10 | 0,3 |   |   |
| 60984 | 1.1/16"  |     |     |    |    |     |   |   |
| 67373 | 1.1/8"   |     | 50  | 16 |    | 0,4 |   |   |
| 60985 | 1.3/16"  | 185 |     |    |    |     |   |   |
| 60986 | 1.1/4"   |     | 55  |    | 11 |     | 5 | 1 |
| 67374 | 1.5/16"  |     |     | 18 |    | 0,5 |   |   |
| 61294 | 1.3/8"   | 210 |     | 19 |    |     |   |   |
| 67375 | 1.7/16"  |     | 60  |    |    |     |   |   |
| 61295 | 1.1/2"   | 220 |     |    |    |     |   |   |
| 61296 | 1.9/16"  |     |     | 20 | 12 | 0,7 |   |   |
| 60987 | 1.5/8"   | 230 | 65  |    |    |     |   |   |
| 67376 | 1.11/16" |     |     |    |    |     |   |   |
| 67377 | 1.3/4"   |     |     |    |    |     |   |   |
| 60988 | 1.13/16" | 240 | 75  | 22 | 13 |     | 1 |   |
| 67378 | 1.7/8"   |     |     |    |    |     |   |   |
| 67379 | 1.15/16" | 250 | 80  | 23 |    |     |   |   |
| 60989 | 2"       |     |     |    |    |     |   |   |
| 67380 | 2.1/16"  |     |     |    | 14 |     |   |   |
| 67381 | 2.1/8"   |     | 85  | 24 |    | 1,4 |   |   |
| 67382 | 2.3/16"  |     |     |    |    |     |   |   |
| 67383 | 2.1/4"   | 270 |     |    |    |     | 1 | - |
| 67384 | 2.5/16"  |     | 90  | 26 | 15 | 1,6 |   |   |
| 60990 | 2.3/8"   |     |     |    |    |     |   |   |
| 67385 | 2.7/16"  |     |     |    |    |     |   |   |
| 67386 | 2.1/2"   |     |     |    |    |     |   |   |
| 60991 | 2.9/16"  | 300 | 100 | 28 | 16 | 2,3 |   |   |
| 67387 | 2.5/8"   |     |     |    |    |     |   |   |
| 67388 | 2.11/16" |     |     |    |    |     |   |   |
| 60992 | 2.3/4"   | 320 | 110 | 32 | 17 | 2,5 |   |   |
| 67389 | 2.13/16" |     |     |    |    |     |   |   |
| 67390 | 2.7/8"   | 330 | 115 | 33 | 18 | 3,2 |   |   |
| 60993 | 2.15/16" |     |     |    |    |     |   |   |

| COD   |          | L   | A   | B  | C  | Kg  |   |   |
|-------|----------|-----|-----|----|----|-----|---|---|
| 60994 | 3"       | 330 | 115 | 33 | 18 | 3,2 |   |   |
| 67391 | 3.1/16"  |     |     |    |    |     |   |   |
| 60995 | 3.1/8"   | 350 | 125 | 34 | 19 | 3,6 |   |   |
| 67392 | 3.1/4"   |     |     |    |    |     |   |   |
| 67393 | 3.5/16"  | 360 | 130 | 36 | 20 | 3,9 |   |   |
| 67394 | 3.3/8"   |     |     |    |    |     |   |   |
| 67395 | 3.1/2"   | 380 | 135 |    |    | 4,8 |   |   |
| 67396 | 3.9/16"  |     |     |    |    |     |   |   |
| 67397 | 3.5/8"   |     |     | 39 | 23 |     |   |   |
| 67398 | 3.11/16" | 390 | 140 |    |    | 5,2 |   |   |
| 60996 | 3.3/4"   |     |     |    |    |     |   |   |
| 67399 | 3.13/16" |     |     |    |    |     |   |   |
| 67400 | 3.7/8"   | 410 | 150 |    |    | 5,8 |   |   |
| 67401 | 3.15/16" |     |     | 43 | 25 |     |   |   |
| 60997 | 4"       |     |     |    |    |     |   |   |
| 67402 | 4.1/16"  | 420 | 155 |    |    | 6,5 |   |   |
| 60998 | 4.1/8"   |     |     |    |    |     |   |   |
| 67403 | 4.3/16"  |     |     |    |    |     |   |   |
| 67404 | 4.1/4"   |     | 160 |    |    | 8   | 1 | - |
| 67405 | 4.5/16"  | 450 |     | 45 | 28 |     |   |   |
| 67406 | 4.3/8"   |     |     |    |    |     |   |   |
| 60999 | 4.1/2"   |     |     |    |    |     |   |   |
| 67407 | 4.9/16"  |     | 170 |    |    | 9,6 |   |   |
| 67408 | 4.5/8"   |     |     |    |    |     |   |   |
| 67409 | 4.11/16" |     |     |    |    |     |   |   |
| 67410 | 4.3/4"   | 480 | 180 | 50 | 30 | 11  |   |   |
| 67411 | 4.13/16" |     |     |    |    |     |   |   |
| 67412 | 4.7/8"   |     |     |    |    |     |   |   |
| 67413 | 4.15/16" |     |     |    |    |     |   |   |
| 67414 | 5"       |     |     |    |    |     |   |   |
| 67415 | 5.1/4"   |     | 200 | 55 | 31 |     |   |   |
| 67416 | 5.5/16"  | 520 |     |    |    | 12  |   |   |
| 67417 | 5.3/8"   |     | 210 |    |    |     |   |   |
| 67418 | 5.1/2"   |     |     | 60 | 32 |     |   |   |
| 67419 | 5.3/4"   | 570 |     |    |    | 14  |   |   |
| 67420 | 6"       | 590 | 220 |    |    | 16  |   |   |

DIN 7444

## TECHNICAL SPECIFICATIONS

| MATERIAL  | Special steel                                            |           |
|-----------|----------------------------------------------------------|-----------|
| HARDNESS  | From 17mm (1/2") to 46mm (1.15/16")                      | 34-40 HRC |
|           | From 50mm (2") to 200mm (6")                             | 30-36 HRC |
| FINISHING | Painted in epoxi powder matt black color semi-texturized |           |