

COMPACT THREADING MACHINE FLARE.4C**MODEL FLARE.4C THREADING MACHINE**

Heavy-duty performance with 1500W induction motor; Threads 1/4"-3/4" at 36RPM,

1-2" at 20RPM, 2-1/2-4" at 11RPM

Easy transport with MH1500 stand

CAPACITY

Pipe: 1/4" -4" (6MM-100MM)

Bolt: 12MM-45MM

SPECIFICATIONS:

Motor: 1500W induction, 50 OR 60Hz single phase

Switch: Heavy-duty rotary Forward/off/reverse and integral foot switch.

Spindle Speed: 36/20/11 RPM.

Front Chuck: Hammer type with replaceable rocker action jaw inserts.

Rear Centering Device: Cam action.

Oiling System: Through the die head, with integral oil

**STANDARD SUPPLY **

Model FLARE.4C Threading Machine. (110 or 220V)

Self-opening die head-SDHN71/SDHB91 (BSPT or NPT) 1/4-2"

Self-opening diehead-SDHN74/SDHB94 (BSPT or NPT) 2-1/2-4"

1/2"-3/4" universal HSS dies set. (BSPT or NPT)

1"-2" universal HSS dies set. (BSPT or NPT)

2-1/2"-4" HS Die set. (BSPT or NPT)

Cutter-MHC2032 : Capacity: 1/4"-4" (6mm-100mm) pipe
Reamer-MHR1010 : Positive-locking, 5-flute cone, righthand 1/4"-4" (6mm-100mm).

*1 Gallon 'Power Fluid PF-9835' cutting oil.

Supplied with MFS642 foot switch, MH1500 wheel stand (Optional)

*May not be supplied to certain countries

CODE	DESCRIPTION	RPM	PIPE	BOLT	KGs
FLARE.4C	WITH 'MH1500' WHEEL STAND 110V OR 220V 50 OR 60Hz (NPT OR BSPT)	36	1/4-4" (6-100MM)	12-50MM	150
FLARE.4C-1	WITH PIPE LEGS 110V OR 220V 50 OR 60Hz (NPT OR BSPT)	36	1/4-4" (6-100MM)	12-50MM	135