METAL WORKING TOOLS / MAG-DRILL



QUALITY DEFINED

MAGNETIC DRILLING MACHINE 50MM, STROC.50HV

Macstroc® industrial Mag-drill 'STROC.50HV' has a cutting capacity of up to 50mm with stepdown gear box , integral auto-cooling function, and supplied with external cooling device. STROC.50HV is equipped with a powerful motor, variable speed function, and the design ensures stable support, faster drilling times and more accurate hole sizing.

KEY FEATURES

- ✓ Variable Speed , Step down gear box
- Stroke up to 220mm from work piece to spindle, enables to attach twist drill chuck and other accessories easily.
- Ensures stable support, faster drilling, low maintenance.
- Minimal vibration, high accuracy and more cutter life.
- MT3 spindle with integrated tool cooling and lubrication



CODE	DESCRIPTION
MPAK-01	pipe adapter kit fixed base 22x12 CM Chain length 29 CM (*Optional)
MAPK-02	pipe adapter kit tilt base 22x12 CM Chain length 29 CM (*Optional)
SF4849	1 GAL, Water soluble multipurpose cutting oil made from virgin base oil. (*Optional)





Annular cutting Ø12-5 Twist drilling Ø1-28 Countersinking Ø10-5 Length & width 210 & 3 Height 440-65 Maximum open from spindle to work piece Stroke 220 Magnetic force 1400 Magnet [L x W x H] 200 x 110 Motor Power 170	
Countersinking Ø10-5 Length & width 210 & 3 Height 440-65 Maximum open from spindle to work piece Stroke 220 Magnetic force 1400 Magnet [L x W x H] 200 x 110	0 mm
Length & width 210 & 3 Height 440-65 Maximum open from spindle to work piece Stroke 220 Magnetic force 1400 Magnet [L x W x H] 200 x 110	Bmm
Height 440-65 Maximum open from 2200 spindle to work piece Stroke 220 Magnetic force 1400 Magnet [L x W x H] 200 x 110	5 mm
Maximum open from spindle to work piece Stroke 220 Magnetic force 1400 Magnet [L x W x H] 200 x 110	60 mm
spindle to work piece 220 Stroke 220 Magnetic force 1400 Magnet [L x W x H] 200 x 110	0mm
Magnetic force 1400 Magnet [L x W x H] 200 x 110	mm
Magnet [L x W x H] 200 x 110	mm
0 1 7	KG
Motor Power 170	x 65 mm
	OW
Speed (no load) 200-650	R/min
Spindle MT-3	MT-2
Voltage 220 –240V or 110V	•
Weight 19 H	(gs

OPTIONAL ACCESSORIES

CODE	DESCRIPTION
ABR.3-B16	Arbor MT-3 - B16
CHUK16-B16	Twist drill chuck 16mm with key



CODE	DESCRIPTION		
CHUK13-A	13MM / 1/2"x20 UNF keyless		
MZXU-01	Adapter For twist-drill chuck 1/2" x 20 UNF - WELDON		

WWW.MACSTROC.CO.UK

INFO@MACSTROC.COM