

COMPACT THREADING MACHINE FLARE.2C



MODEL FLARE.2C THREADING MACHINE

Heavy-duty performance with 1500W motor. Portable/ Light-weight design.

Easy transport and set-up.

Self-Contained Oil System with adjustable flow control.

CAPACITY

Pipe: 1/8" -2"(3MM-50MM)

Bolt: 12MM-50MM

SPECIFICATIONS:

Motor: 1500W universal, 50/60Hz

Switch: Heavy-duty rotary Forward/off/reverse and integral foot switch.

Spindle Speed: 38 RPM.

Front Chuck: Hammer type with replaceable rocker action jaw inserts.

Rear Centering Device: Cam action.

Oiling System: Through the die head, with integral oil reservoir.

Pump: Self-priming constant flow, gerotor pump.

STANDARD SUPPLY ☒

Model FLARE.2C Threading Machine. (110 or 220V)

Self-opening die head-SDH15A (BSPT or NPT)

½"-¾" universal HSS dies set. (BSPT or NPT)

1"-2" universal HSS dies set. (BSPT or NPT)

Cutter-MHC2029 : Capacity: 1/8"-2"(3mm-50mm)

pipe Reamer-MHR1006 : Positive-locking, 5-flute cone, righthand 1/8"-2"(3mm-50mm).

*1 Gallon 'Power Fluid PF-9835' cutting oil.

Supplied with MFS642 foot switch,

MH6511 folding wheel stand (Optional)

*May not be supplied to certain countries

CODE	DESCRIPTION	RPM	PIPE	BOLT	KGs
FLARE.2C	WITH FOLDING TROLLEY WHEEL STAND 110V OR 220V 50/60 (NPT OR BSPT)	38	1/8-2 (3-50MM)	12-50MM	77
FLARE.2C-1	WITH PIPE LEGS 110V OR 220V 50/60 (NPT OR BSPT)	38	1/8-2 (3-50MM)	12-50MM	72