

WE 26-230 MVT Quick (606475000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box; with quick-locking nut, rotating main handle

Order no. 606475000 EAN 4007430268334



Product may differ from Image













- Metabo Marathon motor with patented dust protection for long service life
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic overload protection and restart protection
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor
- LED signal indicates triggered restart protection or overheating

www.metabo.com 1/2



Technical data		
Characteristics		
Disc-Ø	230 mm // 9 "	
Rated input power	2600 W	
Output power	1800 W	
No-load speed	6600 rpm	
Revolutions at rated load	4800 rpm	
Torque	18 Nm / 160 in-lbs	
Spindle thread	M 14	
Weight (without power cable)	6.3 kg / 13.9 lbs	
Cable length	4 m / 13 ft	
Vibration		
Surface grinding	6.4 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Grinding with sandpaper	2.5 m/s ²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	94 dB(A)	
Sound power level (LwA)	105 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Inner support flange

Quick-locking nut

www.metabo.com 2/2