

WEPBA 17-125 Quick RT (601097000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 601097000 EAN 4007430311658



Product may differ from Image






















- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Metabo Marathon-motor with new cooling and carbon brush system for twice the service life
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Reduced vibrations for low-fatigue working thanks to Metabo VibraTech (MVT) side handle and integrated Auto-balancer
- Highest degree of user safety thanks to patented, mechanical disc brake and deadman's switch: disc stop in 2 seconds after releasing even in case of a power cut
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data		
Characteristics		
Disc-Ø	125 mm // 5 "	
Rated input power	1750 W	
Output power	1070 W	
No-load speed	11000 rpm	
Revolutions at rated load	11000 rpm	
Torque	3.8 Nm / 34 in-lbs	
Spindle thread	M 14	
Weight (without power cable)	2.7 kg / 6 lbs	
Cable length	4 m / 13 ft	
Vibration		
Surface grinding	6.1 m/s ²	
Uncertainty of measurement K	1.5 m/s ²	
Grinding with sandpaper	4.4 m/s²	
Uncertainty of measurement K	1.5 m/s ²	
Noise emission		
Sound pressure level	92 dB(A)	
Sound power level (LwA)	103 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Inner support flange

M-Quick flange nut

www.metabo.com 2/2