

KFM 9-3 RF (601751700) Bevelling Tool

(220-240 V / 50 - 60 Hz); MetaLoc

- Compact metal bevelling tool for 45° chamfers and radii of 2 to 3 mm at visible edges
- Surfaces free from oxyd and burrs as ideal preparation for the application of powder or paint coatings for maximum protection from corrosion
- One-touch controller: Patented, tool-free setting of the cutting depth in 0.1 steps; stop points for short setting times, against unintentional adjustment of the cutting depth when working
- Slim cutter head with standard carbide indexable inserts and ball-bearing stationary seal ring for working in tubes and in curves
- Guide stop for uniform finish and high quality of the surface when processing straight sheets
- Metabo Marathon motor with patented dust protection for long service life
- Constamatic (C)-Full wave electronics: fast work progress by means of almost constant speed under load
- Electronic safety shutdown of the motor if the tool jams for safe working
- Electronic overload protection for long service life
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power cut
- Slim housing for ideal handling

[Link to Product](#)

Illustration



Product may differ from Image

System Application Images



Characteristics

No-Load Speed	11500 rpm
Rated Input Power	900 W

Output Power	470 W
Type of edges	Chamfer and radius
Max. chamfer height at 45°	4 mm / 5/32 "
Max. radius	R3
Grading of cutting depth setting	0.1 mm / 0.00394 "
Weight (without power cable)	2.5 kg / 5.5 lbs
Cable Length	4 m / 5/32 "
Noise emission	
Sound Pressure Level	87 dB(A)
Sound power level (LwA)	98 dB(A)
Uncertainty of measurement K	3 dB(A)