

RFEV 19-125 RT (603826710) Renovation Milling Machine

(220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 603826710 EAN 4007430313720



Product may differ from Image









- For effective removal of plaster, adhesive residues, soft screed and old paint from walls, ceilings and floors
- Maximum productivity thanks to top 1,900 Watt with low weight
- Double reduction high-performance gearing for maximum torque and high output
- Fast work progress thanks to large milling diameter
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Cutting depth can be adjusted easily and without the need for tools
- Robust protective cover made from die-cast aluminium with spring-mounted brush rim for low-dust working
- Front handle for safe and uniform guidance when milling, adjustable without tools
- Can be used as renovation grinder on smaller areas when using a diamond cup wheel
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption

www.metabo.com 1/2



Technical data	
Characteristics	
Working width	125 mm
Milling depth	0 - 6 mm // 0 - 1/4 "
Torque	16.8 Nm
No-load speed	750 - 3100 rpm
Rated input power	1900 W
Output power	1240 W
Revolutions at rated load	2800 rpm
Spindle thread	M 14
Weight (without power cable)	3.8 kg / 8.4 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	3.38 m/s²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Bow-type handle

Hexagonal wrench

Plastic carry case

Cutter head pointed (complete)

Flat-pin spanner

www.metabo.com 2 / 2