

BE 751 (600581000) Drill

(220-240 V / 50 - 60 Hz); Cardboard box

- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Rotating carbon brush bridge for maximum performance even in anti-clockwise rotation, e.g. when removing jammed screws
- Vario (V)-electronics for working with customised speeds for the materials used
- Thumbwheel for preselection of speed
- Two-speed gear unit
- Metabo Marathon motor with patented dust protection for long service life
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive if the drill jams for safe working
- Clockwise and anti-clockwise rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Handle with non-slip softgrip surface
- Cable-protecting ball spout for best freedom of motion when working

[Link to Product](#)

Illustration



Product may differ from Image

System Application Images



Characteristics

Rated Input Power	750 W
Output Power	450 W
Drill Ø steel	13 / 8 mm // 1/2 / 0.315 "
Drill-Ø soft wood	40 / 25 mm // 1 5/8 / 1 "

No-Load Speed	0 - 1000 / 0 - 3100 /min
Revolutions at Rated Load	600 / 1800 rpm
Gears	2
Maximum torque	30 / 13 Nm // 266 / 115 in-lbs
Collar Diameter	43 mm / 1 11/16 "
Chuck Capacity	1.5 - 13 mm // 1/16 - 1/2 "
Drill spindle with hexagonal recess	6.35 mm / 1/4 "
Drill Spindle Thread	1/2 " - 20 UNF
Weight (without power cable)	2.7 kg / 6 lbs
Cable Length	4 m / 13 ft
Vibration	
Drilling in metal	4 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound Pressure Level	83 dB(A)
Sound power level (LwA)	94 dB(A)
Uncertainty of measurement K	3 dB(A)