



PRODUCT NUMBER: 2232233  
**POLYTRIL™ MIX**

**Honeywell**

## Overview

**Reference Number**

2232233

**Product Type**

Gloves

**Range**

General purpose

**Line**

Heavy handling

**Brand**

Honeywell

**Brand formerly known as**

SPERIAN

**Industry**

- Automotive and Part Manufacturer
- Aviation
- Building and Construction
- Energy or Electricity
- Iron and steel industry
- Maintenance
- Metal steel
- Mining and Quarrying
- Petro-chemical
- Services
- Ship Building
- Telecoms
- Transportation
- Utilities
- Water treatment
- Wood Industries

**Product Use**

Handling heavy and sharp objects in a greasy, damp and/or dirty environment. General handling in building and public works, steelworks and metallurgy.

## Features & Benefits

**Feature**

Black polyamide/cotton knitted glove. Rough black nitrile coating on palm and fingers. Gauge 10. Length : 25,5 cm.

**Benefit**

**Comfort** The knitting technique helps to obtain a glove that conforms snugly to the hand, with good dexterity. The glove offers maximum comfort and added sturdiness. The tight knit gives the glove perfect support, limits the penetration of dirt and offers a good touch. The ventilated back optimises the glove's breathability. The knitted and elasticated wrist gives the glove good support. **Resistance** The cotton polyamide thread offers excellent comfort and provides the glove with

effective properties against cuts. The nitrile coating at the palm and fingertips provides outstanding abrasion resistance and impermeability to oils. Hygiene Its black colour makes it more soilproof, thus ensuring a longer last.

## Technical Description

### Description

CE CATEGORY : II Intermediary risks In accordance with standards: EN 420-03 Basic standards EN 388-16 Mechanical hazards CHARACTERISTICS : Black polyamide/cotton knitted glove. Rough black nitrile coating on palm and fingers.

### Product Technology

Knitted Coated

### Gauge

10

### Length

25,5 cm

### Harmlessness

In conformity with the European standards.

### Dexterity

Class 5

### Sizes

6 to 11

## EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	4
Cutting resistance (Coupe test)	2
Tear resistance	3
Puncture resistance	2
Cutting resistance (TDM test)	X

## Additional Information

### User Manual

UI 202

## Maintenance

### Storage Information

Minimum packaging : 10 pairs.

Cartons of 100 pairs.

### Care Instructions

This article can be cleaned. For cleaning instructions, please contact Honeywell Safety.