

Power 280-20 W OF (601545000) Power Compressors

Cardboard box

- Compact and mobile piston compressor for flexible use both indoors and at construction sites
- For single phase alternating current
- Oil-free piston sealer: simple transportation and reduced service requirements
- Working pressure can be regulated according to application by means of a pressure reducer with manometer
- Fittings and control elements protected in tubular frames and clearly visible
- Rubberised, stable wheels and pull handle for mobile use
- Wind-up mechanism for the cable
- Good cold start feature by means of push button with safety valve
- Overload protection: protects the motor from overheating
- Rubberised feet for optimum stability
- Attachment and transport option for Metaloc and other common storage case systems
- Crane eyelet for safe and easy transport on the construction site

[Link to Product](#)

Illustration



Product may differ from Image

System Application Images



Characteristics

Suction Rate	280 l/min / 74 gal/h
Filling Capacity	150 / 5.3 cfm
Effective delivery volume (at 80% max. pressure)	140 / 5 cfm
Maximum Pressure	10 bar / 145 psi

Rated Input Power	1.7 kW / 2.5 HP
Maximum speed	2850 rpm
Tank Capacity	20 l / 5.3 gal
Sound pressure level (LpA)	82.5 dB(A)
Dimensions	580 x 600 x 500 mm / 1.9 x 2 x 1.7 ft
Weight	40 kg / 88.2 lbs
Cable Length	4 m / 13 ft
<b>Noise emission</b>	
Sound Pressure Level	82.5 dB(A)
Sound power level (LwA)	97 dB(A)