

**SE 17-200 RT (602259000) Burnishing machine**  
**(220-240 V / 50 - 60 Hz); Cardboard box**

Order no. 602259000  
EAN 4007430323545



Product may differ from Image



- Powerful burnishing machine for sanding, satin-finishing, brushing and high-gloss polishing of e.g. stainless steel
- Maximum productivity thanks to powerful 1,700 Watt motor and high-performance planetary gear train
- Perfect ergonomics thanks to slim handle area for optimal guidance and low-fatigue working
- Metabo Marathon motor with patented dust protection for long service life
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Spindle lock and tool-free flange nut for fast accessory change
- Fast and tool-free adjustment of guard and side handle
- Smooth-running, form-fit mounting arbor for a uniform grinding result
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Auto-stop carbon brushes to protect the motor

## Technical data

### Characteristics

|                              |                         |
|------------------------------|-------------------------|
| Rated input power            | 1700 W                  |
| Output power                 | 1070 W                  |
| Torque                       | 17 Nm / 151 in-lbs      |
| No-load speed                | 800 - 3000 rpm          |
| Spindle thread               | M 14                    |
| Abrasive tool diameter       | 100 - 200 mm // 4 - 8 " |
| Abrasive tool width          | 50 - 100 mm // 2 - 4 "  |
| Weight (without power cable) | 2.9 kg / 6.4 lbs        |
| Cable length                 | 4 m / 13 ft             |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Satin-finish                 | 3.8 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 91 dB(A)  |
| Sound power level (LwA)      | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Side handle